

LANmark-OF DB Outdoor PE 2-144core APAC Region

- Suitable for outdoor application in ducts or direct burial
- Robust structure with water-blocking material
- Fiber available in OM3/OM4/G.652.D/G.657.A1, up to 144 cores
- Double metal tape armoring provides full rodent protection
- Loose tube with gel

DESCRIPTION


DB outdoor cable is suitable for outdoor application in ducts or direct burial. The cable is watertight due to the gel in the loose tube and water-blocking material in cable. It consists of double metal tape armoring providing full rodent protection. The cable outer jacket is PE, UV-resistant and good weatherability. Diameter of the fibers is 250 um. Termination of fibers can be done with splicing of pigtailed.

- Mechanical resistance to impacts: IEC 60794-1
- Crush resistance : IEC 60794-1
- Operating temperature : -40 - 70°C
- Storage temperature : -40 - 70°C

Construction

Legend accompanying the crossing section drawing:

1. Optical fibers (250um)
2. Tube filling compound
3. Loose tube
4. Aluminum tape armor
5. Water-blocking gel
6. PE outer jacket
7. Steel tape armor
8. PE inner jacket
9. Filler
10. Central strength member
11. Water-blocking gel



STANDARDS

ANSI/TIA-568-C.3
IEC 60793-2-10
ISO/IEC 11801

LANmark-OF DB Outdoor PE 2-144core APAC Region

CHARACTERISTICS

Construction characteristics

Armour type	Double Metal Tape
Outer sheath	PE
Sheath colour	Black

Mechanical characteristics

Crush resistance (IEC 60794-1-E3)	300 N/cm
Maximum pulling force (IEC 60794-1-2-E1)	3000 N
Mechanical resistance to impacts (IEC 60794-1-E4)	10 impacts of 10 N.m

Usage characteristics

Ambient installation temperature, range	0...40 °C
Minimum dynamic operating bending radius	166 mm
Minimum static operating bending radius	332 mm
Operating temperature, range	-40...70 °C
Storage temperature, range	-40...70 °C

Product list

Aginode ref.	Country ref.	Name
N174.06DBPE	-	LANmark-OF Outdoor DB optical fiber cable,Singlemode G.652.D 9/125 6F,PE,Black, APAC Region
N174.12DBPE	-	LANmark-OF Outdoor DB optical fiber cable,Singlemode G.652.D 9/125 12F,PE,Black, APAC Region
N175.06DBPE	-	LANmark-OF Outdoor DB optical fiber cable,Mutimode OM3 50/125 6F,PE,Black, APAC Region
N175.12DBPE	-	LANmark-OF Outdoor DB optical fiber cable,Mutimode OM3 50/125 12F,PE,Black, APAC Region
N174.96DBPE	-	LANmark-OF Outdoor DB optical fiber cable,Singlemode G.652.D 9/125 96F,PE,Black, APAC Region

☎ = Make to order, 📦 = In Stock

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.