LANmark-6A ULTIM UniBoot Patch Cords

LANMARK-6A ULTIM PATCH CORD CAT 6A SCREENED LSZH 2M ORANGE



Aginode Ref: N11A.U1F020OK

- High speed RJ45 patch cord to run 10GBase-T and future Category 6A / Class EA applications
- High Density support : 48 cords on 1 height unit
- Frequency range up to 500 MHz, fully compliant with TIA 568.2-D and ISO 11801 for Category 6A
- Individually screened pairs for excellent NEXT performance and Alien Crosstalk immunity
- Certified by 3rd party lab
- Removable latch protector available in 8 colours for colour coding

STANDARDS

ANSI/TIA-568-C.2
EN 50173-1
IEEE 802.3an
ISO/IEC 11801
ISO/IEC TR24750
TIA/EIA TSB-155

Application

LANmark-6A Ultim cords are developed to support 10 Gigabit Ethernet (IEEE 802.3an) and any other future Cat.6A application.

LANmark-6A Ultim Cords offer superior performance up to 500MHz and are matched with other LANmark-6A components to provide improved data throughput in complex channel configurations. Ultim cords use stranded cable and as such provide maximum system flexibility for the use at Cross Connects and Consolidation points.

They will also maximise the lifetime and longevity of the system by minimising the risk of wear & tear damage. Due to their good electrical performance and mechanical stability, LANmark-6A Ultim cords can be used for accurate field testing of Cat 6A cabling channels.

Ultim Cords feature a slim boot for mechanical protection, which is kept inside the RJ45 boundaries to enable High Density Patching with 48 cords in 1 height unit.

They also come with a ‘Replaceable’ Latch Protector, which can be used for colour coding of different services.

Performance

The LANmark-6A Ultim cords fully comply and exceed the requirements of EIA/TIA-568.2-D and ISO11801 and enable to achieve high performing Cat 6A channels. Used with other

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

LANmark-6A components, very short Cat 6A link and channel configurations with up to 3 connection points within 10 meters can be supported.

Guarantees

When installed in combination with other LANmark-6A components, a 25 years channel warranty can be obtained, covering full 10GBase-T support and full Cat 6A/Class EA compliance.

Usage

- The cords are by design fully Alien Crosstalk compliant, so no special installation rules need to be taken into account for ANEXT and AFEXT compliance.
- 1, 2, 3, 5, 10, 20m are standard lengths available from stock; other lengths are available on demand.
- Orange (N11A.U1FxxxOK) and Dark Grey (N11A.U1FxxxDK) are standard colours available from stock. Other colours available as make-to-order are:
  Blue (N11A.U1FxxxBK) / Red (N11A.U1FxxxRK) / Yellow (N11A.U1FxxxYK) / Green (N11A.U1FxxxGK).
  White (N11A.U1FxxxWK) and Black (N11A.U1FxxxKK) are available on demand.
- Default Plug Configuration is a black boot with a preinstalled black latch protector.

Electrical Performance LANmark-6A 4 Connector Channel

Freq	Attn in dB		NEXT in dB			PSNEXT in dB			ACR-F in dB	
in MHz	Max	Typ	Std	Min	Typ	Std	Min	Typ	Std	Typ
1	<4	4,0	65,0	67,0	85,0	62,0	64,0	74,8	63,3	69,9
4	4,1	4,1	63,0	65,0	72,9	60,5	62,5	65,0	51,2	57,9
10	6,4	6,3	56,6	58,6	65,0	54,0	56,0	58,5	43,3	49,9
16	8,1	8,0	53,2	55,2	60,9	50,6	52,6	55,1	39,2	45,9
20	9,1	9,0	51,6	53,6	59,0	49,0	51,0	53,5	37,2	43,9
31,25	11,4	11,2	48,4	50,4	55,1	45,7	47,7	50,2	33,4	40,0
62,5	16,3	15,9	43,4	45,4	49,1	40,6	42,6	45,1	27,3	34,0
100	20,8	20,2	39,9	41,9	45,0	37,1	39,1	41,6	23,3	29,9
155	26,2	25,4	36,7	38,7	41,2	33,8	35,8	38,3	19,5	26,1
200	30,0	28,9	34,8	36,8	39,0	31,9	33,9	36,4	17,2	23,9
250	33,8	32,5	33,1	35,1	37,0	30,2	32,2	34,7	15,3	22,0
300	37,3	35,7	31,7	33,7	35,4	28,8	30,8	33,3	13,7	20,4
500	49,3	46,7	27,9	29,9	31,0	24,8	26,8	24,9	9,3	16,0

Freq	PS ACR-F in dB		PS ANEXT in dB			PS AACR-F in dB			RL in dB		
in MHz	Std	Typ	Std	Min	Typ	Std	Min	Typ	Std	Min	Typ
1	60,3	66,9	80,0	90,0	92,0	77,0	92,0	94,0	19,0	21,0	21,0
4	48,2	54,9	74,0	89,0	91,0	65,0	80,0	82,0	19,0	21,0	32,0
10	40,3	46,9	70,0	85,0	87,0	57,0	72,0	74,0	19,0	21,0	28,0
16	36,2	42,9	68,0	83,0	85,0	52,9	67,9	69,9	18,0	20,0	26,0
20	34,2	40,9	67,0	82,0	84,0	51,0	66,0	68,0	17,5	19,5	25,0
31,25	30,4	37,0	65,1	80,1	82,1	47,1	62,1	64,1	16,5	18,5	23,1
62,5	24,3	31,0	62,0	77,0	79,0	41,1	56,1	58,1	14,0	16,0	20,0
100	20,3	26,9	60,0	75,0	77,0	37,0	52,0	54,0	12,0	14,0	18,0
155	16,5	23,1	57,1	72,1	74,1	33,2	48,2	50,2	10,1	12,1	16,1
200	14,2	20,9	55,5	70,5	72,5	31,0	46,0	48,0	9,0	11,0	15,0
250	12,3	19,0	54,0	69,0	71,0	29,0	44,0	46,0	8,0	10,0	14,0
300	10,7	17,4	52,8	67,8	69,8	27,5	42,5	44,5	7,2	9,2	13,2
500	6,3	13,0	49,5	64,5	66,5	23,0	38,0	40,0	6,0	8,0	11,0

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

All values are based on Worst Case 4 Connector Channel configurations according to ISO11801.
Minimum and maximum values represent guaranteed Channel performance.
Standard values based on ISO11801 Class EA

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

LANmark-6A Ultim Patch Cord Cat 6A Screened LSZH 2m Orange

Characteristics

Construction characteristics	
Colour	Orange
Screen	Yes
Outer sheath	LSZH
Dimensional characteristics	
Conductor cross-section (AWG/KCMIL)	26
Nominal outer diameter (mm)	6.0 mm
Electrical characteristics	
Characteristic impedance	100 Ohm
Usage characteristics	
Range	LANmark-6A
Field of application	Indoor
Length	2 m
Category	Cat. 6A
Flame retardant	IEC 60332-1
Component function	Patchcord
Packaging	Box of 50 items
Mechanical durability/matings	750

Documentation

Freetable LM6A Channel V2 Part 1_1.xls xls — 20.5 KB Download

Freetable LM6A Channel V2 Part 2_1_1.xls xls — 24.5 KB Download

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.