Essential-6 Patch Panels

ESSENTIAL-6 PCB PATCH PANEL UNSCREENED 24 RJ45 CAT 6 REAR CONNECT BLACK

Aginode Ref: N500.206

- Complies to the latest Category 6 standard
- 24 unshielded RJ45 on 1U
- Punchdown termination from the rear
- Colour: Black
- UL listed
- Supplied with fixings, cable ties and cable stripping tool



STANDARDS

IEC 60603-7-4
ISO/IEC 11801

Application

The Essential-6 Rear Connect Panel is based on 19 inch frame dimensions and has 24 Category 6 RJ45 ports on 1U. It supports all Class E applications up to 250 MHz. When installed in conjunction with Essential-6 cable and outlets, a 25 year Class E Link Warranty can be obtained through the Aginode website.

Design

The Essential-6 Rear Connect Panel is compatible with the complete Essential-6 range and is designed to be used with unshielded Category 6 cable with solid wire from 24 to 22 AWG. The panel has a textured black finishing. The RJ45 ports have screen-printed numbering 1-24 and a labeling surface for patch panel identification is foreseen on the right-hand side of each panel.

Performance

The Essential-6 patch panels are compliant with the specifications of ISO/IEC 11801 and IEC 60603-7.

Installation

- Fast and easy termination of IDC blocks with 110 or LSA+ punchdown tool
- Wiring according to colour code T568A or T568B.
- Supplied with fixings, cable ties and cable stripping tool.

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

- For detailed installation instructions, please refer to the Instruction Sheet enclosed with every panel.

Contact resistance:	max. 20 m Ohm
Input to output DC resistance:	max. 200 m Ohm
Insulation resistance:	min. 500 M Ohm
Voltage proof:	1000 V DC or AC peak, contact to contact
Mating cycles:	min. 750
Insertion cycles:	min. 20
Insertion and withdrawal force:	max. 20 N

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

Essential-6 PCB Patch Panel Unscreened 24 RJ45 Cat 6 Rear Connect Black

Characteristics

Construction characteristics	
Connector type	RJ45 and 110/LSA+ IDC
Dimensional characteristics	
Heightunit	1 U
Usage characteristics	
Category	Cat. 6
Component function	Patch panel
Number of ports	24
Range	essential-6

Documentation

Freetable Cat6 UNSHIELDED connectors additional characteristics.xls xls — 22 KB Download

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.