# LANmark-6A Cable

**LANMARK-6A F/FTP DUAL AWG23 CAT 6A LSZH CCA S1A D1 A1 ORANGE 500M REEL**

**Aginode Ref:** N100.693G-OC

- Ideal cable for 10GBase-T application
- Full compliance to latest standards for Category 6A and Class EA
- Guaranteed performance up to 500MHz
- Individual pair shielding offering Alien Crosstalk immunity
- Dual version permits two cables to be installed in one go
- Enhanced reaction-to-fire performance according to CPR classification Cca-s1a,d1,a1 (h/EN50575:2014+A1:2016)



## STANDARDS

ISO/IEC 11801
ANSI/TIA 568.2-D
EN 50173-1
EN 50288-4-1
IEC 61156-5
IEC 60332-3
IEEE 802.3bt (PoE++)

## Application

LANmark-6A cables are the ideal solution for a 10G Ethernet network. The range has been designed specifically to support the higher frequencies required for 10 Gigabit Ethernet, while maintaining full backwards compatibility with today's needs. All LANmark-6A cables are shielded, in order to ensure immunity to Alien Crosstalk and other external interferences.

- 10Base-T Ethernet
- 100Base-TX Fast Ethernet
- 1000Base-TX Gigabit Ethernet
- 10GBase-T 10 Gigabit Ethernet IEEE 802.3
- 155 Mbit ATM
- 1.2 Gbit ATM
- future Cat 6A and Class EA applications
- PoE++ Type 4 (IEEE 802.3bt)

## Performance

With guaranteed performance to 500MHz, Aginode LANmark-6A cables exceed the requirements of the International, European and American cable standards, including ISO/IEC 11801, IEC 61156-5, EN 50173, EN 50288 and TIA/EIA 568.2-D

When used in combination with Aginode LANmark-6A connectors and LANmark-6A Ultim patch cords, the system supports the 10GBase-T applications as defined in IEEE 802.3an and meets or exceeds the link and channel

*All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.*

requirements for Category 6A and Class EA as defined in TIA/EIA 568.2-D and ISO/IEC 11801.

# Installation

To support the correct set-up of hand held analysers for installation testing, the actual cable NVP value is given in the cable's print legend.

# Guarantees

Traceability codes on both cable and packaging ensure quality validation of the installed cable.

Installations with LANmark-6A cable and connectivity are qualified for a 25 year full system warranty, which includes Parts, Channel Performance, Application Support and Labour, as described in the Aginode Certified System Warranty.

## Electrical Performance LANmark-6A FFTP Cable

| Freq | Attn | | NEXT | | PSNEXT | | ACR-F | | PS ACR-F | | PS ANEXT | | PS AACR-F | | RL | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| in MHz | in dB | | in dB | | in dB | | in dB | | in dB | | in dB | | in dB | | in dB | |
| | Max. | Typ. | Min. | Typ. | Min. | Typ. | Min. | Typ. | Min. | Typ. | Min. | Typ. | Min. | Typ. | Min. | Typ. |
| **1** | 2,1 | 2,1 | 74,3 | 104,3 | 72,3 | 102,3 | 67,8 | 92,8 | 64,8 | 89,8 | 67,0 | 90,0 | 67,0 | 76,7 | 20,0 | 26,0 |
| **4** | 3,8 | 3,8 | 65,3 | 95,3 | 63,3 | 93,3 | 55,8 | 80,8 | 52,8 | 77,8 | 67,0 | 90,0 | 66,2 | 75,9 | 23,0 | 29,0 |
| **10** | 5,9 | 5,9 | 59,3 | 89,3 | 57,3 | 87,3 | 47,8 | 72,8 | 44,8 | 69,8 | 67,0 | 87,0 | 58,2 | 67,9 | 25,0 | 31,0 |
| **16** | 7,5 | 7,5 | 56,2 | 86,2 | 54,2 | 84,2 | 43,7 | 68,7 | 40,7 | 65,7 | 67,0 | 85,0 | 54,1 | 63,8 | 25,0 | 31,0 |
| **20** | 8,4 | 8,4 | 54,8 | 84,8 | 52,8 | 82,8 | 41,8 | 66,8 | 38,8 | 63,8 | 67,0 | 84,0 | 52,2 | 61,9 | 25,0 | 31,0 |
| **31,25** | 10,5 | 10,5 | 51,9 | 81,9 | 49,9 | 79,9 | 37,9 | 62,9 | 34,9 | 59,9 | 67,0 | 82,1 | 48,3 | 58,0 | 23,6 | 29,6 |
| **62,5** | 15,0 | 15,0 | 47,4 | 77,4 | 45,4 | 75,4 | 31,9 | 56,9 | 28,9 | 53,9 | 65,6 | 79,0 | 42,3 | 52,0 | 21,5 | 27,5 |
| **100** | 19,1 | 19,1 | 44,3 | 74,3 | 42,3 | 72,3 | 27,8 | 52,8 | 24,8 | 49,8 | 62,5 | 77,0 | 38,2 | 47,9 | 20,1 | 26,1 |
| **155** | 24,1 | 24,1 | 41,4 | 71,4 | 39,4 | 69,4 | 24,0 | 49,0 | 21,0 | 46,0 | 59,6 | 74,1 | 34,4 | 44,1 | 18,8 | 24,8 |
| **200** | 27,6 | 27,6 | 39,8 | 69,8 | 37,8 | 67,8 | 21,8 | 46,8 | 18,8 | 43,8 | 58,0 | 72,5 | 32,2 | 41,9 | 18,0 | 24,0 |
| **250** | 31,1 | 31,1 | 38,3 | 68,3 | 36,3 | 66,3 | 19,8 | 44,8 | 16,8 | 41,8 | 56,5 | 71,0 | 30,2 | 39,9 | 17,3 | 23,3 |
| **300** | 34,3 | 34,3 | 37,1 | 67,1 | 35,1 | 65,1 | 18,3 | 43,3 | 15,3 | 40,3 | 55,3 | 69,8 | 28,7 | 38,4 | 16,8 | 22,8 |
| **500** | 45,3 | 45,3 | 33,8 | 63,8 | 31,8 | 61,8 | 13,8 | 38,8 | 10,8 | 35,8 | 52,0 | 66,5 | 24,2 | 33,9 | 15,2 | 21,2 |

*All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.*

# LANmark-6A F/FTP Dual AWG23 Cat 6A LSZH Cca s1a d1 a1 Orange 500m reel

## Characteristics

| | |
|---|---|
| **Construction characteristics** | |
| Colour | Orange |
| Outer sheath | LSZH |
| Type of cable | F/FTP |
| **Dimensional characteristics** | |
| Approximate weight | 100 kg/km |
| Conductor cross-section (AWG/KCMIL) | 23 |
| Diameter over insulation | 1.36 mm |
| Nominal outer diameter (mm) | 7.7 mm |
| **Electrical characteristics** | |
| Characteristic impedance | 100 Ohm |
| Max. DC resistance of the conductor at 20°C | 80 Ohm/km |
| Max. transfer impedance at 30 MHz (Ohm/km) | 120 Ohm/km |
| Mutual capacitance | 45 nF/km |
| **Mechanical characteristics** | |
| Maximum operating pulling force | 100 N |
| **Transmission characteristics** | |
| Coupling attenuation at 30 MHz | >85 dB |
| Nominal Velocity of Propagation (NVP) | 82 % |
| Propagation delay, max. 100 MHz | 536 ns/100m |
| Skew | 30 ns/100m |
| **Usage characteristics** | |
| Ambient installation temperature, range | -10...60 °C |
| Category | Cat. 6A |
| Flame retardant | IEC 60332-1 |
| Gases corrosivity | IEC 60754-1; IEC 60754-2 |

*All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.*

| | |
|---|---|
| Length | 500 m |
| Minimum Bend Radius - During Installation (under Tension) | 62 mm |
| Minimum Bend Radius - Installed | 31 mm |
| Operating temperature, range | -20...60 °C |
| Packaging | Reel |
| Range | LANmark-6A |
| Smoke density | IEC 61034 |

## Documentation

Freetable LM6A FFTP V3.xls xls — 25.5 KB Download

## Declaration of Performance

LANmark-6A F/FTP Dual AWG23 Cat 6A LSZH Cca s1a d1 a1 Orange 500m reel pdf — 141.42 KB Download

*All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.*