Supporting Kits

FIBREROUTE 120MM(4.75 INCH) MOUNTING BOTTOM BAR KIT

Aginode Ref: N350.003SMB1

Aginode Fibre Trunking System provides a dedicated pathway for fibre optic cables and cords to protect them from accidental damage. The system offers a flexible, high-capacity solution for data centre containment which is easy to install and reconfigure to meet future needs.

- Mounting kits available for various data centre installation environments
- Supporting Bar for Trapeze/hanging style mounting, can be use when the thread rod is already installed on site.

120mm(4.75 inch) Mounting Bottom Bar Kit includes crosspiece and screws . N350.003SMB1 is available for 120mm(4.75 inch) series. Distance between center of mounting holes on the crosspiece is 250mm(9.85"). Total length of the crosspiece is 300mm(12").



STANDARDS

EN 50173-5
ISO/IEC 24764

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

FIBREROUTE 120mm(4.75 inch) Mounting Bottom Bar Kit

Characteristics

Construction characteristics	
Colour	Metalic
Material	Steel
Dimensional characteristics	
Approximate net weight	1.8 kg
Usage characteristics	
Operating temperature, range	-25...60 °C
Storage temperature, range	-45...60 °C

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.