WALLDROP V2

WALLDROP V2 12OF (SLIM TRAY)





Aginode Ref: WALLDROP (slim tray)

WALLDROP V2 (slim tray) is equipped with one SLIM splice cassette supporting 12 optical fibers.

Available colors:

- Black: 14500785
- Grey: 14500786

Included sealing kits:

- For distribution cables: 10–12 mm
- For drop cables: 5–7 mm

Note:
The SLIM cassette has a thickness of 9.8 mm and is compatible with the 48FO extension kit, allowing the addition of three extra trays. It is not compatible with the 36FO extension kit, which includes two additional STANDARD trays.

WALLDROP V2 (Slim Tray) is a compact, low-profile wall-mounted enclosure designed for façade fiber-optic cable deployment with minimal visual impact. It supports connections for up to 10 subscribers and is equipped with a 12-splice SLIM cassette, which can be upgraded in the field to a 48-fiber capacity using an expansion kit.

The enclosure is suitable for micro-module extraction from inline cables or as a transition point for feeding and drop cables. Optional accesories are available to secure cable strength members and/or aramid yarns, enabling its use as a junction box.

Cable sealing and entry options:

- Drop cable entries utilize rubber seals with sealing plugs for cable diameters between 3 and 7 mm (3–5 mm and 5–7 mm seal options).
- Inline cable entries are protected by lateral split seals accommodating cable diameters from 6 to 12 mm (available in 6–8 mm, 8–10 mm, and 10–12 mm versions).

STANDARDS

Aginode specification

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

The integrated organizer tray features dedicated storage areas for both extracted fibers or micro-modules from the feeder cable and subscriber connections. The main cable is securely fixed externally using cable clamps.

The splice cassette includes a dedicated slot for a 1x4 bare-fiber splitter. The splitter is optional.

WALLDROP V2 offers flexible installation options and can be mounted horizontally, vertically, or directly suspended from the cable, depending on deployment requirements.

Each unit is supplied with all necessary installation accessories, including:

- Combs
- Splice cassette
- Seals
- Cable ties
- Wall-mounting kit
- Window Protection Clip for safeguarding the cable jacket opening created during micro-module extraction

The product is available in Light Grey and Black.





Window Protection Clip (WPC)

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

WALLDROP V2 12OF (slim tray)

Characteristics

Construction characteristics	
Material	Thermoplastic
Dimensional characteristics	
Diameter branch cable	5...7 mm
Diameter main cable	10...12 mm
Height	48 mm
Length	203 mm
Max. number of cables	10
Max. number of cassettes	1
Splice number	12
Width	138 mm
Mechanical characteristics	
IK Rating	8
Usage characteristics	
Installation type	Outdoor
Minimum static operating bending radius	15 mm
Operating temperature, range	-40...65 °C
Packaging	Box
RoHS compliant	Yes
U.V resistance	Yes
Watertightness	IP 55

Documentation

Instruction manual pdf — 5.25 MB Download

Leaflet Facade Solution EN pdf — 5.07 MB Download

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.