
# essential-OF TB LSZH 2-24C - APAC Region

**ESSENTIAL-OF TIGHT BUFFER LSZH BI OM3 4C ORANGE**




**Aginode Ref:** N275.TBIN04O

Tight buffered optical fibre cables

- Indoor cable designed for backbone/horizontal installation
- Available in OM3 and SingleMode G.652.D
- Outer Jacket is Low Smoke Zero Halogene (LSZH)

### Description and Application

Essential-OF TB Indoor fibre cable is designed for indoor applications especially for building. The fibre cable has 900µm tight buffered fibres. The cable is coated with aramid yarns, and the outer jacket is LSZH with good fire performance. Essential-OF TB is available for Bend Insensitive OM3 and SingleMode G.652.D.

The fibre cable is of a dry structure suitable for horizontal or vertical installation. The fibre cable meets the needs of indoor fire protection and can be installed in ducts.

• Can be installed both vertically or horizontally

• Applicable as standard multimode and singlemode fibre

• LSZH Jacket

• Tight buffered fibre

### Construction

Legend accompanying the cross section drawing for 2-24core OF cable:

1. 900µm Tight buffered fibre
2. Aramid yarn
3. LSZH jacket materials

## STANDARDS

ANSI/TIA-568-C.3
IEC 60332-1
IEC 60332-3-24 Cat.C
IEC 60793-2-10
ISO/IEC 11801

*All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.*

# Essential-OF Tight Buffer LSZH BI OM3 4C ORANGE

## Characteristics

| | |
|---|---|
| **Construction characteristics** | |
| Colour | Orange |
| Fiber optic type | OM3 50/125 |
| **Dimensional characteristics** | |
| Outer Diameter | 4.5 mm |
| Number of optical fibres | 4 |
| **Mechanical characteristics** | |
| Mechanical resistance to impacts (IEC 60794-1-E4) | 100 impacts of 1 N.m |
| Crush resistance (IEC 60794-1-E3) | 1000 N/100mm |
| Maximum pulling force (IEC 60794-1-2-E1) | 440 N |
| **Usage characteristics** | |
| Operating temperature, range | -20...60 °C |
| Minimum dynamic operating bending radius | 90.0 mm |
| Minimum static operating bending radius | 45 mm |
| Storage temperature, range | -20...60 °C |
| Installation temperature, range | 0...40 °C |

*All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.*