

# LANmark-OF UC Outdoor PE 2-24core APAC Region

LANMARK-OF UC PE 24CORE SM G.652.D BLACK APAC REGION

**Aginode Ref:** N174.191

Suitable for in ducts or direct burial

- Corrugated steel tape armour
- Gel filled tube
- Available to multimode and singlemode fibre
- Provides rodent protection
- Outer Jacket is HDPE

## Description and Application

Aginode LANmark-OF UC fibre cable is designed for outdoor applications. The construction is suitable for use outdoor for direct burial. It consists of a Unitube structure protected by corrugated steel tape armouring, the Unitube can hold up to 24C fibres. This provides rodent protection and high crush resistance. The cable has a HDPE outer jacket.

## Construction

Legend accompanying the cross section drawing:

1. Optical fibres (250 um)
2. Waterproof gel filling
3. Loose tube
4. Glass Yarn
5. Corrugated steel tape armour
6. HDPE outer jacket with UV resistant additive

## Characteristics

- Designed for termination by splicing
- Central loose tube design
- Corrugated steel protection
- Waterproof structure and UV-resistant
- Available in Multimode and Singlemode fibre
- Available from 2-24 fibres



## STANDARDS

ANSI/TIA-568-C.3  
IEC 60793-2-10  
ISO/IEC 11801

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

# LANmark-OF UC PE 24core SM G.652.D Black APAC Region

## Characteristics

### Construction characteristics

|                  |                        |
|------------------|------------------------|
| Fiber optic type | SM (G.652D)            |
| Armour type      | Galvanized steel tapes |
| Outer sheath     | HDPE                   |
| Sheath colour    | Black                  |

### Dimensional characteristics

|                          |        |
|--------------------------|--------|
| Outer Diameter           | 9.2 mm |
| Number of optical fibres | 24     |

### Mechanical characteristics

|                                                   |                      |
|---------------------------------------------------|----------------------|
| Mechanical resistance to impacts (IEC 60794-1-E4) | 100 impacts of 1 N.m |
| Maximum pulling force (IEC 60794-1-2-E1)          | 1300 N               |
| Crush resistance (IEC 60794-1-E3)                 | 300 N/cm             |

### Usage characteristics

|                                          |             |
|------------------------------------------|-------------|
| Operating temperature, range             | -20...60 °C |
| Minimum dynamic operating bending radius | 184.0 mm    |
| Minimum static operating bending radius  | 92 mm       |
| Storage temperature, range               | -30...60 °C |
| Ambient installation temperature, range  | 0...40 °C   |

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.