
LANmark-OF TB OFNP 2-48C - APAC Region

LANMARK-OF TIGHT BUFFER INDOOR 24X MULTIMODE 50/125 BI OM3 PLENUM, OFNP



Aginode Ref: N175.031NP

- Tight Buffer Indoor optical fiber cables Indoor cable
- Aramid yarns for ease of installation
- Design for direct termination and splicing
- 24 fibers
- Bending Insensitive Fibers for OM3 cables

Application

The LANmark-OF Tight buffer Indoor has 900 um buffered fibres. This second
coating till 900 um provides additional protection of the fibres and facilitates the
handling when terminating the fibres in a patch panel. The easy strip tight buffer
design allows stripping the fibre over 10 cm in one action.
The LANmark-OF Tight buffer Indoor is most suitable for direct termination by
either anaerobic or hot melt connectors. The tight buffered fibres can also be
terminated with splicing of pigtails.
The dry structure of the LANmark-Of Tight Buffer Indoor allows both vertical and
horizontal installations. It complies with the indoor fibre requirements. The cables
can also be installed in a duct by pulling.

Construction

Legend accompanying the cross section drawing:

1. Optical fibre (900 um)
2. Aramid Yarns
3. Outer sheath in PVC OFNP material

STANDARDS

ANSI/TIA-568-C.3
IEC 60793-2-10
ISO/IEC 11801

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

LANmark-OF Tight Buffer Indoor 24x Multimode 50/125 BI OM3 Plenum, OFNP

Characteristics

Construction characteristics	
Fiber optic type	OM3 50/125
Colour	Orange
Dimensional characteristics	
Number of optical fibres	24
Outer Diameter	8.1 mm
Weight	60 g
Mechanical characteristics	
Mechanical resistance to impacts (IEC 60794-1-E4)	100 impacts of 1 N.m
Maximum pulling force (IEC 60794-1-2-E1)	660 N
Crush resistance (IEC 60794-1-E3)	1000 N/100mm
Usage characteristics	
Installation temperature, range	0...40 °C
Storage temperature, range	-30...70 °C
Operating temperature, range	-20...60 °C
Minimum dynamic operating bending radius	162.0 mm
Minimum static operating bending radius	81 mm

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.