

LANmark-OF Sliding Patch Panels APAC

LANMARK-OF 24 PORTS SLIDING PATCH PANEL, SNAP-IN MODULE, INTEGRATED CABLE MANAGER, 1U, WHITE

Aginode Ref: N441.303

Aginode new LANmark-OF SNAP-IN series patch panel can be installed in standard 19"inch cabinets or patch frames. The patch panel is compatible with various SNAP-IN connectors and the high-density design can support termination up to 48-core fiber cable in 1U space. This patch panel also supports copper cable connectors and can be used as multimedia patch panel. The front integrated cable manager with label for orderly management of patch cords which bringing significant improvements resulting in better customer experience when networks to be deployed.

Features

24 ports for SNAP-IN format, can hold 24 SNAP-IN Adaptors and accept up to 48 fibers in 1U. Support the mixed use of fiber / copper

3 possible positions for the front: flush, flat or recessed. Base plate is limited to prevent the tray from falling out. Fully stable, no risk of movement when patching

Front integrated cable manager with label for orderly management of patch cords

Provide ample fixing positioning for cable glands and tie-wraps. Multiple supporting gland holes at the back to hold incoming OF cables. Gland sizes: 25mm

Improved Splice tray handling. Equipped with a full set splice tray, supporting up to 48 fibers splicing, The splice tray can be installed in 2 position left or right according to the use space.

Professional Better Look and feel

2 version available: Black (N441.304) or White (N441.303)

Compatibility

Suitable for tight buffer cables (direct termination) or Loose tube cables using Splice Cassette; Accomodate perfectly Pre-terminated assemblies by means of bendable plates; Accepting LANmark-OF snap-in adapters DLC, SC, DSC or copper module; Supports up to 48 fibres when Duplex LC adapters are used.



STANDARDS

ISO/IEC 11801

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

LANmark-OF 24 Ports Sliding Patch Panel, Snap-In Module, integrated Cable Manager, 1U, White

Characteristics

Dimensional characteristics

Depth	300 mm
Width	19 inches
Heightunit	1 U