

# LANmark-OF UC Outdoor LSZH 2-24core APAC Region

## LANMARK-OF UC LSZH 4CORE OM5 BLACK

### Aginode Ref: N179.471

- Suitable for in ducts or direct burial
- Corrugated steel tape armour
- Gel filled tube
- Available to multimode and singlemode fibre
- Provides rodent protection
- Outer Jacket is Low Smoke Zero Halogene (LSZH)

### Description and Application

Aginode LANmark-OF UC fibre cable is designed for outdoor applications. The construction is suitable for use outdoor for direct burial. It consists of a Unitube structure protected by corrugated steel tape armouring, the Unitube can hold up to 24C fibres. This provides rodent protection and high crush resistance. The cable has a LSZH outer jacket.

### Construction

Legend accompanying the cross section drawing:

1. Optical fibres (250 um)
2. Waterproof gel filling
3. Loose tube
4. Glass Yarn
5. Corrugated steel tape armour
6. LSZH outer jacket with UV resistant additive

### Characteristics

- Flame retardant (IEC 60332-1) and fire retardant (IEC 60332-3-24)
- Designed for termination by splicing
- Central loose tube design
- Corrugated steel protection
- Waterproof structure and UV-resistant
- Available in Multimode and Singlemode fibre



### STANDARDS

2014/68/EU

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

- Available from 2-24 fibres

*All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.*

# LANmark-OF UC LSZH 4core OM5 Black

## Characteristics

### Construction characteristics

|                  |                     |
|------------------|---------------------|
| Fiber optic type | OM5 50/125 Wideband |
| Armour type      | Corrugated steel    |
| Outer sheath     | LSZH                |
| Sheath colour    | Black               |

### Dimensional characteristics

|                          |        |
|--------------------------|--------|
| Outer Diameter           | 9.3 mm |
| Number of optical fibres | 4      |

### Mechanical characteristics

|   |                     |
|---|---------------------|
| Mechanical resistance to impacts (IEC 60794-1-E4) | 100 impacts of 3N.m |
| Crush resistance (IEC 60794-1-E3)                 | 3000 N/100mm        |
| Maximum pulling force (IEC 60794-1-2-E1)          | 1300 N              |

### Usage characteristics

|  |             |
|--|-------------|
| Operating temperature, range             | -20...60 °C |
| Minimum dynamic operating bending radius | 186.0 mm    |
| Minimum static operating bending radius  | 93 mm       |
| Storage temperature, range               | -30...60 °C |
| Ambient installation temperature, range  | 0...40 °C   |

## Documentation

LANmark-UC LSZH 24C APAC-Dimensional & Mechanical.xlsx xlsx — 9.32 KB [Download](#) ↓

N-number for LMOF UC LSZH-APAC\_2-24.xlsx xlsx — 9.65 KB [Download](#) ↓