

FLOWGUARD™ - Fire Resistant - Multibundle Cables

FLOWGUARD LSZH 6X12 SM-D SP1905 BK

Aginode Ref: 14501232

Multi micro-modules cable with dielectric FRP armour:

This FLOWGUARD™ (ref. SP1905) is designed for indoor/outdoor installation in railways/tunnel infrastructure or public buildings when circuit integrity during fire is a key point.

The FRP armour provides a high rodent protection. This cable has an outstanding fire behaviour.

This cable can be operated under a wide temperature range.

FLOWGUARD™ is fire resistant (circuit integrity) following EN50200 during 120minutes.

Waterproof dry core structure.

Design

The FLOWGUARD™ LSZH* cable has a central strength member (FRP : Fibre Reinforced Plastic), with bundles around. The design is reinforced by a first layer of aramid yarns, a LSZH* inner sheath, a FRP composed armour and a LSZH* outer sheath.


A ripcord is placed beneath the inner and outer sheath for an easy access to the micro-modules.

Technical performances

The cable performances are specified in the following tables.

Additional details

This cable is provided as a standard with a black sheath and FOTAG bundle color coding.



STANDARDS

EN 50200
EN 50399
IEC 60332-1
IEC 60332-3
IEC 60754-2
IEC 60794
IEC 61034

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

Euroclass

B2^{ca} s1a d1 a1

Marking

Aginode FLOWGUARD FIBRE OPTIC CABLE LSZH - SP1905 -
XXxYY - TN - metric

XX = Fibre Count YY = Fibre Type TN = Traceability Number

FLOWGUARD LSZH 6X12 SM-D SP1905 BK

Characteristics

Construction characteristics

Additional strength member	Aramide
Armour type	FRP
Colour	Black
Construction type	Multibundle
Fiber optic type	SM
Halogen free	IEC 60754-1
Material used for longitudinal water tightness	Swellable yarn
Metal free	Yes
Outer sheath	LSZH
Strength member	Central FRP

Dimensional characteristics

Approximate weight	200 kg/km
Nominal outer diameter (mm)	12.4 mm
Number of optical fibres	72
Number of tubes	6

Mechanical characteristics

Crush resistance (IEC 60794-1-E3)	300 N/cm
Maximum installation tension	5000 N
Mechanical resistance to impacts	10 impacts of 3 N.m

Transmission characteristics

Attenuation, max. 1310 nm (cabled)	0.36 dB/1000m
Attenuation, max. 1550 nm (cabled)	0.23 dB/1000m

Usage characteristics

Bending factor when laying	20 (xD)
Fire resistant	UNE-EN50200 PH120
Fire retardant	IEC 60332-3
Flame retardant	IEC 60332-1
Installation temperature, range	-5...40 °C
Installation type	Indoor/Outdoor

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

Minimum static operating bending radius	200 mm
Operating temperature, range	-40...70 °C
Rodent protection	FRP
Smoke density	IEC 61034-2
Storage temperature, range	-40...70 °C

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.