

# Outlets: @XS-Fast

## OUTLETS: @XS-FAST

### Aginode Ref: TBD

- Up to 2 SC/LC adapters
- Wall mounted, on flush box, on a DIN rail and on most of the electrical equipment mounting supports on the market
- No lid-opening to fix the outlet
- Ready-to-fix kit in option

### Application

By default, it is designed for flush wall mounting. It can also be adapted for use with DIN rails and most standard electrical mounting systems available on the market by means of an optional adapter plate. The @XS-FAST can additionally serve as a DTIO, acting as the termination point of the operator's access network.

### Functional characteristics

The OTO can be installed with a pre-connected drop cable entering from either side, the bottom, or the rear. It features a dedicated splicing area and fibre management zone, enabling cable-to-cable or cable-to-pigtails splicing.



## STANDARDS

Aginode specification

# Outlets: @XS-FAST

## Characteristics

### Construction characteristics

Colour	White RAL 9010
Material	Thermoplastic

### Dimensional characteristics

Depth	18 mm
Height	80 mm
Maximum number of adaptators	2
Splice number	2
Width	80 mm

### Mechanical characteristics

IK Rating	5
-----------	---

### Usage characteristics

Adaptor	SC/LC
Fire resistant	UL 94 V0
Minimum static operating bending radius	15 mm
Operating temperature, range	-5...45 °C
Packaging	Paper bag
U.V resistance	Yes
Watertightness	IP 50

ABS 1594 -FAST PTO.pdf pdf — 981.89 KB [Download](#) ↓