

Outlets: @XS-Fast

OUTLETS: @XS-FAST

Aginode Ref: TBD

- Up to 2 SC/LC adapters
- Wall mounted, on flush box, on a DIN rail and on most of the electrical equipment mounting supports on the market
- No lid-opening to fix the outlet
- Ready-to-fix kit in option

Application

By default, it is designed for flush wall mounting. It can also be adapted for use with DIN rails and most standard electrical mounting systems available on the market by means of an optional adapter plate. The @XS-FAST can additionally serve as a DTIO, acting as the termination point of the operator's access network.

Functional characteristics

The OTO can be installed with a pre-connected drop cable entering from either side, the bottom, or the rear. It features a dedicated splicing area and fibre management zone, enabling cable-to-cable or cable-to-pigtails splicing.



STANDARDS

Aginode specification

Outlets: @XS-FAST

Characteristics

Construction characteristics

| | |
|----------|----------------|
| Colour | White RAL 9010 |
| Material | Thermoplastic |

Dimensional characteristics

| | |
|------------------------------|-------|
| Depth | 18 mm |
| Height | 80 mm |
| Maximum number of adaptators | 2 |
| Splice number | 2 |
| Width | 80 mm |

Mechanical characteristics

| | |
|-----------|---|
| IK Rating | 5 |
|-----------|---|

Usage characteristics

| | |
|---|------------|
| Adaptor | SC/LC |
| Fire resistant | UL 94 V0 |
| Minimum static operating bending radius | 15 mm |
| Operating temperature, range | -5...45 °C |
| Packaging | Paper bag |
| U.V resistance | Yes |
| Watertightness | IP 50 |

ABS 1594 -FAST PTO.pdf pdf — 981.89 KB [Download](#) ↓