

WLB-Med : Indoor Wall Box

WLB-MED - STANDARD

Aginode Ref: NWLB.M010DU.W

The WLB-Med is a compact and efficient fiber management solution designed for passive infrastructure cabling and other indoor fiber networks. It ensures secure connectivity, high-density fiber management, and easy maintenance.

Key Features


- **10 SC ports** for high-density connectivity
- **Two internal cassettes** for organized fiber routing
- **Wall-mounted, space-saving design**
- **IP42-rated enclosure** for dust and moisture protection
- **Quick-access cover** for simplified maintenance

Product Consistency

Standard : Ready for custom configurations.

Applications

- Passive fiber optic infrastructure networks(GPON & P2P, FTTO...cet)
- Wall-mounted fiber distribution point for structured cabling



STANDARDS

Aginode specification

WLB-Med - Standard

Characteristics

Construction characteristics

Fiber optic type	SM (G.652)
------------------	------------

Dimensional characteristics

Depth	42 mm
-------	-------

Height	180 mm
--------	--------

Width	125 m
-------	-------

Mechanical characteristics

IK Rating	8
-----------	---

Usage characteristics

Fire resistant	UL 94 V0
----------------	----------

Operating temperature, range	-10...60 °C
------------------------------	-------------

Watertightness	IP44
----------------	------