

# DCmark Rack Unit Solution Server DC

## DCMARK RACK UNIT SOLUTION SERVER DC 42U 800X1000

### **Aginode Ref:** NRCK.420810440-B

The DCmark RUS NRCK.420810440-B is a high-performance server rack engineered for optimal airflow thanks to his high perforation ration at 80%. With the need of IA and GPU server more and more heavy, the DCmark rack metallic frame is designed to support high loading capacity :

- Loading capacity up to 1500kg to support heavy server
- Perforation ratio at 80% to offer a perfect air flow
- Double doors for a better access
- Lateral cable manager to ensure easy cable management and high reliability
- optional : rear support for intelligent PDU and internal lateral cable tray

The NRCK.42081044-B, offer a height of 42U with a depth of 1000mm and width of 800mm

The DCmark RUS NRCK.420810440-B is a high-performance server rack engineered for optimal airflow thanks to his high perforation ration at 80%. With the need of IA and GPU server more and more heavy, the DCmark rack metallic frame is designed to support high loading capacity up to 1500kg.

Equipped with several features and smart cable management, DCmark Rack Unit Solution will ensure reliability, easy installation & easy maintenance for DC technician. The cable management will ensure good cable management and ensure perfect bending radius for cable and patch cord in order to offer the best performance especially for fiber optical cable.

The double front door will offer a full access to the cabling in order to facilitate all technical intevention inside the rack. The doors are equipped with a 3 locking points system closing to ensure high security level. Smart handle with RFDI card can be also installed to avoid key management.

The NRCK.42081044-B, offer a height of 42U with a depth of 1000mm and width of 800mm



# DCmark Rack Unit Solution Server DC 42U 800x1000

## Characteristics

### Construction characteristics

Cabinet format	19"
Cable entry	From the top through brush panel and from bottom through sliding access
Cabling management	Lateral front cable manager
Colour	Black
Material	Steel
Rack version	Server
Type of front door	double perforated at 80%
Type of rear door	double perforated at 80%

### Dimensional characteristics

19" mounting	front & rear
Approximate net weight	121 kg
Depth	1000 mm
Height	2017 mm
Heightunit	42 U
Width	800 m

### Mechanical characteristics

IK Rating	07
-----------	----

### Usage characteristics

Locking system	3 locking points with mechanical handle
Packaging	carton