

DCmark Rack Unit Solution Collocation DC

DCMARK RACK UNIT SOLUTION COLLOCATION DC 42U 2 COMPARTMENTS

Aginode Ref: NRL2.420808340-B

DCmark RUS-Collocation DC rack is designed to maximize security, flexibility, and efficient space utilization in shared data center environments. Their reinforced structure and advanced access control options ensure reliable isolation between tenants. Engineered for seamless integration, clean cabling, and scalable growth.

Rack are equipped with 2 compartment of 20U; each have a single front perforated door, lockable by key. Each key have a specific number for the confidentiality.

Cable entries with brush panel equipped the roof and serve the different compartment through closed cable ducts to offer a high level of security and avoid having access to the cable to all the tenants.

DCmark RUS-Collocation DC rack is designed to maximize security, flexibility, and efficient space utilization in shared data center environments. Their reinforced structure and advanced access control options ensure reliable isolation between tenants. Engineered for seamless integration, clean cabling, and scalable growth.

The Rack NRCL2 is equipped with 2 compartments of 20U with a total loading capacity of 1500Kg. Each compartment have a single front perforated door and double rear perforated door.

To ensure a high confidentiality of the tenant, each compartment have is own key with a specific number printed on the barrel (Aginode is the only part knowing the correspondance between this code and the key number).

Cable entries with brush panel equipped the roof and serve the different compartment through closed cable ducts to offer a high level of security and avoid having access to the cable to all the tenants.



DCmark Rack Unit Solution Collocation DC 42U 2 compartments

Characteristics

Construction characteristics

Cabinet format	19"
Compartment number	2x20U
Colour	Black
Cable entry	Entrée supérieure via passe-fil balai et chemin de câble fermé
Material	Steel
Rack version	Collocation
Type of front door	Simple porte AV perforée
Type of rear door	Double porte AR perforée

Dimensional characteristics

19" mounting	Avant & Arrière
Compartment Height U	20U
Height	2017 mm
Width	800 mm
Approximate net weight	128 kg
Depth	800 mm
Heightunit	42 U

Mechanical characteristics

IK Rating	07
-----------	----

Usage characteristics

Locking system	Clé individuelle par compartiment
IP Rating	IP20
Key type	Numéro spécifique & unique