

LANmark-OF UC Outdoor PE 2-24core APAC Region

LANMARK-OF UC PE 12CORE SM G.657.A1 BLACK APAC REGION

Aginode Ref: N17A.185

Suitable for in ducts or direct burial

- Corrugated steel tape armour
- Gel filled tube
- Available to multimode and singlemode fibre
- Provides rodent protection
- Outer Jacket is HDPE

Description and Application

Aginode LANmark-OF UC fibre cable is designed for outdoor applications. The construction is suitable for use outdoor for direct burial. It consists of a Unitube structure protected by corrugated steel tape armouring, the Unitube can hold up to 24C fibres. This provides rodent protection and high crush resistance. The cable has a HDPE outer jacket.

Construction

Legend accompanying the cross section drawing:

1. Optical fibres (250 um)
2. Waterproof gel filling
3. Loose tube
4. Glass Yarn
5. Corrugated steel tape armour
6. HDPE outer jacket with UV resistant additive

Characteristics

- Designed for termination by splicing
- Central loose tube design
- Corrugated steel protection
- Waterproof structure and UV-resistant
- Available in Multimode and Singlemode fibre
- Available from 2-24 fibres



STANDARDS

ANSI/TIA-568-C.3
IEC 60793-2-10
ISO/IEC 11801

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

LANmark-OF UC PE 12core SM G.657.A1 Black APAC Region

Characteristics

Construction characteristics

| | |
|---------------|------------------------|
| Armour type | Galvanized steel tapes |
| Outer sheath | HDPE |
| Sheath colour | Black |

Mechanical characteristics

| | |
|--|----------|
| Crush resistance (IEC 60794-1-E3) | 300 N/cm |
| Maximum pulling force (IEC 60794-1-2-E1) | 1300 N |

Usage characteristics

| | |
|--|-------------|
| Ambient installation temperature, range | 0...40 °C |
| Minimum dynamic operating bending radius | 164.0 mm |
| Minimum static operating bending radius | 82 mm |
| Operating temperature, range | -20...60 °C |
| Storage temperature, range | -30...60 °C |