

DCmark Rack Unit Solution Server DC

DCMARK RACK UNIT SOLUTION SERVER DC 47U 800X1000

Aginode Ref: NRCK.470810440-B

The DCmark RUS NRCK.470810440-B is a high-performance server rack engineered for optimal airflow thanks to his high perforation ration at 80%. With the need of IA and GPU server more and more heavy, the DCmark rack metallic frame is designed to support high loading capacity :

- Loading capacity up to 1500kg to support heavy server
- Perforation ratio at 80% to offer a perfect air flow
- Double doors for a better access
- Lateral cable manager to ensure easy cable management and high reliability
- optional : rear support for intelligent PDU and internal lateral cable tray


The NRCK.47081044-B, offer a height of 47U with a depth of 1000mm and width of 800mm

The DCmark RUS NRCK.470810440-B is a high-performance server rack engineered for optimal airflow thanks to his high perforation ration at 80%. With the need of IA and GPU server more and more heavy, the DCmark rack metallic frame is designed to support high loading capacity up to 1500kg.

Equipped with several features and smart cable management, DCmark Rack Unit Solution will ensure reliability, easy installation & easy maintenance for DC technician. The cable management will ensure good cable management and ensure perfect bending radius for cable and patch cord in order to offer the best performance especially for fiber optical cable.

The double front door will offer a full access to the cabling in order to facilitate all technical intevention inside the rack. The doors are equipped with a 3 locking points system closing to ensure high security level. Smart handle with RFDI card can be also installed to avoid key management.

The NRCK.47081044-B, offer a height of 47U with a depth of 1000mm and width of 800mm



DCmark Rack Unit Solution Server DC 47U 800x1000

Characteristics

Construction characteristics

Cabinet format	19"
Cabling management	Gestion de câble latérale
Colour	Black
Cable entry	Entrée supérieure via passe-fil balai et accès par la base
Material	Steel
Rack version	Server
Type of front door	Double porte AV perforée
Type of rear door	Double porte AR perforée

Dimensional characteristics

19" mounting	Avant & Arrière
Height	2195 mm
Width	800 mm
Approximate net weight	146 kg
Depth	1000 mm
Heightunit	47 U

Mechanical characteristics

IK Rating	07
-----------	----

Usage characteristics

Packaging	carton
Locking system	3 points de fermeture avec poigné