

# LANmark-OF DB Outdoor PE 2-144core APAC Region

LANMARK-OF OUTDOOR DB OPTICAL FIBER CABLE,SINGLEMODE G.652.D 9/125 96F,PE,BLACK, APAC REGION

## Aginode Ref: N174.96DBPE

- Suitable for outdoor application in ducts or direct burial
- Robust structure with water-blocking material
- Fiber available in OM3/OM4/G.652.D/G.657.A1, up to 144 cores
- Double metal tape armoring provides full rodent protection
- Loose tube with gel

## DESCRIPTION

DB outdoor cable is suitable for outdoor application in ducts or direct burial. The cable is watertight due to the gel in the loose tube and water-blocking material in cable. It consists of double metal tape armoring providing full rodent protection. The cable outer jacket is PE, UV-resistant and good weatherability. Diameter of the fibers is 250 um. Termination of fibers can be done with splicing of pigtailed.

## Construction

Legend accompanying the crossing section drawing:

1. Optical fibers (250um)
2. Tube filling compound
3. Loose tube
4. Aluminum tape armor
5. Water-blocking gel
6. PE outer jacket
7. Steel tape armor
8. PE inner jacket
9. Filler
10. Central strength member
11. Water-blocking gel



## STANDARDS

ANSI/TIA-568.3-D  
IEC 60794  
ISO 11801 Ed.3

# LANmark-OF Outdoor DB optical fiber cable, Singlemode G.652.D 9/125 96F, PE, Black, APAC Region

## Characteristics

### Construction characteristics

Armour type	双层金属带
Outer sheath	PE
Sheath colour	Black

### Mechanical characteristics

Crush resistance (IEC 60794-1-E3)	300 N/cm
Maximum pulling force (IEC 60794-1-2-E1)	3000 N
Mechanical resistance to impacts (IEC 60794-1-E4)	10 impacts of 10 N.m

### Usage characteristics

Ambient installation temperature, range	0...40 °C
Minimum dynamic operating bending radius	151 mm
Minimum static operating bending radius	302 mm
Operating temperature, range	-40...70 °C
Storage temperature, range	-40...70 °C