essential-OF Fixed Patch Panels SP(Selected Package) Version

ESSENTIAL-OF 1U 24-PORT PATCH PANEL,12 DUPLEX LC ADAPTERS AND 24 OM3 MM PIGTAILS,WITH MOUNTING AND SPLICING ACCESSORIES,BLACK

Aginode Ref: N441.5SPL24

- 1U Fixed Patch Panels with standard adaptors for wide compatibility
- Up to 24 simplex SC or duplex LC adapters
- Ready to use configuration, equipped with 12 duplex LC adapters and 24 OM3 MM pigtails
- Delivered with all accessories like splicing set and mounting screw set.
- The rear end latch is convenient for removing the upper cover plate
- White silkscreen label above each ports
- Suitable for 19-inch cabinets and racks installation



STANDARDS

ANSI/TIA-568.3-D
ISO/IEC 11801

essential-OF fixed patch panel SP(Selected Package) Version from Aginode, which is simple and easy to operate resulting in better customer experience. Typical installation conditions for the Aginode' essential-OF Fixed Patch Panel are backbones for offices, campus, and small data centers, while providing the required density, it also provides simplicity and flexibility.

The patch panel designed with duplex LC or simplex SC standard adaptors, and delivered with pigtails and accessories.
SP(Selected Package) Version covered the most popular configuration for quick deployment on site. please refer to detailed characteristics.

Multiple cables can be fixed in the rear of the tray with tie wraps, and there are 4 slots with a diameter of 20mm at the rear end.

The Fixed Patch Panels suitable for 19-inch cabinets and racks installation, the surface is fully painted black frosted ink jet.

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

essential-OF 1U 24-port patch panel,12 duplex LC adapters and 24 OM3 MM pigtails,with mounting and splicing accessories,black

Characteristics

Construction characteristics	
Fibre Type Connector	LC/UPC
Fiber optic type	OM3 50/125
Dimensional characteristics	
Width	19 inches
Depth	235 mm
Heightunit	1 U
Usage characteristics	
Adaptor	Duplex LC MM Aqua

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.