

LANmark-OF MPO-MPO fibre patch cord OFNP

LANMARK-OF MPO PATCH CORD OM4 METHODB MPO12/PC FEMALE - MPO12/PC FEMALE 12CORE LSZH AQUA ULTRA LOW LOSS 10M

Aginode Ref: N125.7SUAxxxNP

- Aginode MPO patch cord adopts a slim cable design with OD of 3mm, this gives Datacenter user 19% more room in cable management in front of the panel
- The optical performance of Aginode MPO connector is better than industry level and can meet international standards
- 12F indoor flexible optical cable
- Available for Single Mode and bend insensitive OM3/OM4
- Flame retardant performance met the OFNP standard according to UL 1651
- Straight polarity (Type B) according to TIA 568.3-E standard, Key Up/Key UP orientation
- Female MPO connectors both end

Applications

Aginode MPO patch cords is designed to support Datacenter high speed network applications like 40G, 100G, 200G and 400G. Aginode' low loss optical performance can support at least 6 MPO connection to allow intermediate distributors in mega Datacenters. The MPO cable is optimized for OD and remain good pulling force and crush performance. Each MPO trunk is delivered with test report by factory to ensure performance.

Features

- MPO connectors met IEC 61754-7-1 and GR-1435-CORE standards
- MPO connector for Multimode is PC and MPO connector for Singlemode is APC
- Flame retardant performance met the OFNP standard according to UL 1651
- Fibre can met IEC 60793-2-10 (A1a.3b OM4)

Optical performance and polarity



STANDARDS

ANSI/TIA-568.3-D
ISO/IEC 11801

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

- Typical insertion loss for a Ultra low-loss multimode MPO connector is 0.15 dB with a maximum of 0.25 dB insertion loss.
- Typical insertion loss for a low-loss singlemode MPO connector is 0.35 dB with a maximum of 0.5 dB insertion loss.
- The insertion loss of a MPO connector is measured according to standard IEC 61300-3-45.
- The minimum return loss for a multimode MPO connection is 20 dB . The minimum return loss for a singlemode MPO connection is 55 dB. The measurement is according to IEC 61300-3-6.

LANmark-OF MPO Patch Cord OM4 MethodB MPO12/PC Female - MPO12/PC Female 12Core LSZH Aqua Ultra Low Loss 10m

Characteristics

Construction characteristics

Fiber optic type	OM4 50/125
Jacket color	Aqua

Dimensional characteristics

Number of optical fibres	12
--------------------------	----

Transmission characteristics

Insertion Loss, maximum, dB	0.25 dB
Return Loss, Minimum, dB	20 dB

Usage characteristics

Operating temperature, range	-20...60 °C
------------------------------	-------------