LANmark-OF MPO-MPO fibre patch cord OFNP

LANMARK-OF MPO-MPO PATCH CORD, OM4, STRAIGHT, MPO FEMALE-MPO FEMALE, 12CORE, OFNP, VIOLET, ULTRA LOW LOSS, XM



Aginode Ref: N125.7SUVxNP

- Aginode MPO patch cord adopts a slim cable design with OD of 3mm，this gives Datacenter user 19% more room in cable management in front of the panel
- The optical performance of Aginode MPO connector is better than industry level and can met international standards
- 12F indoor flexible optical cable
- Ultra low loss 0.25dB
- Available for bend insensitive OM4
- Straight polarity (Type B) according to TIA 568.3-E
- Female MPO connectors both end

STANDARDS

ANSI/TIA-568-C.3
ISO/IEC 11801

Application

Aginode MPO patch cords is designed to support Datacenter high speed networkapplications like 40G, 100G, 200G and 400G. Aginode' low loss opticalperformance can support at least 6 MPO connection to allow intermediatedistributors in mega Datacenters. The MPO cable is optimized for OD andremain good pulling force and crush performance. Each MPO trunk is deliveredwith test report by factory to ensure performance.

Features

- MPO connectors met IEC 61754-7-1 and GR-1435-CORE standards
- MPO connector for Multimode is PC
- Flame retardant performance met the OFNP standard according to UL 1651
- Fibre can met IEC 60793-2-10 (A1a.3b OM4)

Optical performance and polarity

- Typical insertion loss for a Ultra low-loss multimode MPO connector is 0.15 dB with a maximum of 0.25 dB insertion loss.
- Typical insertion loss for a low-loss singlemode MPO connector is 0.35 dB with a maximum of 0.5 dB insertion loss.
- The insertion loss of a MPO connector is measured according to standard IEC 61300-3-45.

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

- The minimum return loss for a multimode MPO connection is 20 dB . The minimum return loss for a singlemode MPO connection is 55 dB. The measurement is according to IEC 61300-3-6.

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

LANmark-OF MPO-MPO patch cord, OM4, Straight, MPO Female-MPO female, 12core, OFNP, Violet, Ultra Low loss, xm

Characteristics

Construction characteristics	
Fiber optic type	OM4 50/125
Jacket color	Violet
Dimensional characteristics	
Number of optical fibres	12
Transmission characteristics	
Insertion Loss, maximum, dB	0.25 dB
Return Loss, Minimum, dB	20 dB
Usage characteristics	
Operating temperature, range	-20...60 °C

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.