LANmark 工业跳线 RJ45 IP67/IP20 Cat 6A



STANDARDS

ISO/IEC 11801

应用

LANmark工业IP67/IP20跳线旨在与LANmark工业IP65/67插座一起使用。在工业和恶劣环境下，它可提供无液体和灰尘的安全连接。

跳线的IP20端可连接到任何具有标准RJ45端口的IT或工业设备。

LANmark工业跳线可用于在工业区提供完整的端到端E级或EA级解决方案。

性能

- 高速跳线
- 可靠的连接
- 完全符合ISO/IEC11801（通用布线 - 工业场所）

根据 ISO/IEC 11801:2002 的定义，LANmark 工业跳线在衰减（插入损耗）、NEXT/FEXT、功率和 NEXT/FEXT 和回波损耗方面表现出色。

这就提高了数据吞吐量。

因此，它支持 Cat 5E、Cat 6 和 Cat 6A 所定义的所有数据应用，如

- 10baseT
- 快速以太网
- 千兆以太网
- 155 ATM
- 622 ATM
- 1.2 ATM
- **工业以太网**。

跳线的 IP67/IP20 端部采用推拉式引导。它具有 IP67 防护等级和跳线锁定系统。只有当用户拉动保护罩时，跳线才能从插座中拔出。拉动电线是无法将电线拔出的。这种推拉式锁定套符合 ISO/IEC24702 和 IEC 61073-3-106（8 路工业连接器）标准。

安装

- 具有良好化学和机械性能的 PVC 电缆。
- 可用长度：1.5 - 3.0 - 5.0 和 10 米。
- 可提供 10 米长的 IP67 单端电缆。
- 结构坚固。
- 特殊护套使接头保持力强。
- 外部应力消除
- IP67 推拉锁定系统

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

Product list

	Aginode ref.	Country ref.	Name
	N10i.E34DJ	-	LANmark Industry patch cord RJ45 IP67/IP20 Category 6A screened PVC 1.5m Yellow
	N10i.E34FJ	-	LANmark Industry patch cord RJ45 IP67/IP20 Category 6A screened PVC 3m Yellow
	N10i.E34HJ	-	LANmark Industry patch cord RJ45 IP67/IP20 Category 6A screened PVC 5m Yellow
	N10i.E34OJ	-	LANmark Industry patch cord RJ45 IP67/IP20 Category 6A screened PVC 10m Yellow

= Make to order, = In Stock

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.