

# Essential-6 U/UTP Cable

- Unshielded construction
- Complies to the latest Category 6 standards
- Supports Class E applications up to 250 MHz.
- Central cross maintains geometry and performance

## Application

The Aginode Essential-6 cables are manufactured and tested to the latest Category 6 specifications. They are compatible with the complete Essential-6 modular and PCB connectivity range. When the cable is installed in conjunction with Essential-6 outlets and patch panels, a 25 year Class E Link Certificate can be obtained from the Aginode website.

## Design

The Essential-6 cables have 24 AWG solid copper wires and comply with IEC 60228. The PE central cross filler keeps the pairs in place and reduces the risks of losing performance when bending the cable.

The cables are available with a Light Grey PVC or an Orange LSZH outer jacket.


## Performance

Aginode Essential-6 cables are compliant with the requirements of the International, European and American cable standards, including ISO/IEC 11801, IEC 61156-5, EN 50173, EN 50288 and TIA/EIA 568-C.2.

## Installation

The Essential-6 cables are as easy to install as their Category 5e equivalent, due to their small nominal outer diameter.

To support the correct set-up of hand held analysers for installation testing, the actual cable NVP value is given in the cable's print legend.



## STANDARDS

ANSI/TIA-568-C.2  
ISO/IEC 11801

# Essential-6 U/UTP Cable

## CHARACTERISTICS

### 结构特性

外护套

低烟无卤

电缆类型

U/UTP

### 使用特性

范围




essential-6



## Resources

### 文件

Freetable Ess6 channel.xls xls — 14 KB [下载](#) ↓

## Product list

	Aginode ref.	Country ref.	Name	外护套	电缆类型
	N100.161-OE	-	Essential-6 U/UTP AWG24 Cat 6 LSZH Eca Orange 305m box	低烟无卤	U/UTP
	N100.164-OE	-	Essential-6 U/UTP AWG24 Cat 6 LSZH Eca Orange 500m reel	低烟无卤	U/UTP
	N100.166-LE	-	Essential-6 U/UTP AWG24 Cat 6 PVC Eca Light Grey 305m box	聚氯乙烯	U/UTP

 = Make to order,  = In Stock

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.