LANmark-10G 跳线

- 高速 RJ45 跳线，可运行 10GBase-T 和未来的 Cat6A 应用
- 高密度支持：1 个高度单元上有 48 根跳线
- 频率范围高达 500MHz
- 改装闩式保护器有 8 种颜色可供选择，以便进行颜色编码

应用

LANmark-10G跳线用于支持万兆以太网（IEEE 802.3an）和任何其他未来的Cat.6A应用。它们提供高达500MHz的稳定性能，并与其他LANmark-10G组件相匹配，在通道配置中提供更高的数据吞吐量。10G跳线使用绞合电缆，因此为交叉连接和合并点的使用提供了最大的系统灵活性。

LANmark-10G 连接线具有用于机械保护的超薄保护罩，保护罩位于 RJ45 边界内，可在 1 个高度单位内实现 48 条连接线的高密度配接。它们还配有 "可更换 "闩锁保护器，可用于不同服务的颜色编码。

性能

LANmark-10G 跳线完全符合 EIA/TIA-568-C.2 和 ISO11801 的要求，可实现 Cat 6A 通道。

使用方法

- 该跳线设计符合异形串扰标准，因此无需考虑特殊的安装规则以符合 ANEXT 和 AFEXT 标准。
- 1、2、3、5、10 米是现货供应的标准长度，其他长度可按需提供。
- 标准护套颜色为橙色。其他颜色可按需提供。
- 默认插头配置为带预装黑色闩式保护器的黑色插头。

STANDARDS

EN 50173-1
IEEE 802.3an
ISO/IEC 11801
ISO/IEC TR24750
TIA/EIA TSB-155
ANSI/TIA 568.2-D

电气性能 LANmark-10G EA级通道

Freq (MHz)	Attn (dB)	NEXT (dB)	PSNEXT (dB)	ACR-F (dB)	PS ACR-F (dB)	PS ANEXT (dB)	PS AACR-F (dB)	RL (dB)
1	2,3	65,0	62,0	63,3	60,3	67,0	64,7	19,0
4	4,2	63,0	60,5	51,2	48,2	67,0	64,7	19,0
10	6,5	56,6	54,0	43,3	40,3	67,0	57,0	19,0
16	8,2	53,2	50,6	39,2	36,2	67,0	52,9	18,0
20	9,2	51,6	49,0	37,2	34,2	67,0	51,0	17,5
31,25	11,5	48,4	45,7	33,4	30,4	65,1	47,1	16,5
62,5	16,4	43,4	40,6	27,3	24,3	62,0	41,1	14,0
100	20,9	39,9	37,1	23,3	20,3	60,0	37,0	12,0
155	26,3	36,7	33,8	19,5	16,5	57,1	33,2	10,1
200	30,1	34,8	31,9	17,2	14,2	55,5	31,0	9,0
250	33,9	33,1	30,2	15,3	12,3	54,0	29,0	8,0
300	37,4	31,7	28,8	13,7	10,7	52,8	27,5	7,2
500	49,3	27,9	24,8	9,3	6,3	49,5	23,0	6,0

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

LANmark-10G 跳线

CHARACTERISTICS

结构特性	
颜色	橙
屏蔽	是
外护套	低烟无卤
使用特性	
范围	LANmark-10G
长度	1 m

Resources

文件

10G channel unformatted_3.xlsx xlsx — 9.74 KB 下载

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

Product list

	Aginode ref.	Country ref.	Name	颜色	外护套	屏蔽	长度
	N10G.P1B010OK	-	LANmark-10G Patch Cord Cat 6A Screened LSZH 1m Orange	橙	低烟无卤	是	1 (m)
	N10G.P1B020OK	-	LANmark-10G Patch Cord Cat 6A Screened LSZH 2m Orange	橙	低烟无卤	是	2 (m)
	N10G.P1B030OK	-	LANmark-10G Patch Cord Cat 6A Screened LSZH 3m Orange	橙	低烟无卤	是	3 (m)
	N10G.P1B050OK	-	LANmark-10G Patch Cord Cat 6A Screened LSZH 5m Orange	橙	低烟无卤	是	5 (m)

= Make to order, = In Stock

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.