LANmark-OF Micro-Bundle Universal (144F) Cca

- Micro-Bundle Universal optical fibre cable with High Level of Fire Performance
- Reaction to fire Cca -s1a,d0,a1 according to EN50575:2014+A1:2016
- Indoor cable and outdoor installation in a duct
- Fully waterproof and rodent resistant
- Small, but mechancial strong cable
- Bundle extraction over 2 meters
- Designed for splicing with pigtails



STANDARDS

ISO/IEC 11801

Description and Application

The new Micro-Bundle technology from Aginode allows to manufacture a flexible and small tube. This Micro-Bundle is the central part of the new “LANmark-OF Micro-Bundle Universal” cable design. Each Micro-Bundle contains 12 fibres with a fibre diameter of 250 um. Termination of these fibres is done with splicing with pigtails.

Several Micro-Bundles are arranged around a central strength element. The combination of the Micro-Bundle technology, the central strength element and the glass yarns result in a mechanical robust, but also in a small and flexible cable.
The small bending radius of the LANmark-OF Micro-Bundle Universal makes the cable easy to arrange in patch panels, in cable trays and in ducts.

The watertight glass yarns and the very limited amount of gel inside the tube make the LANmark-OF Micro-Bundle Universal design watertight, rodent resistant and suitable for installation outdoor in a duct by pulling.

The LANmark-OF Micro-Bundle Universal complies with the indoor fire requirements. Since there is no drip effect of the very limited amount of gel the cable is optimised for both horizontal and vertical installations.

Construction

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

Legend accompanying the cross section drawing:

1. Central strength element
2. Optical fibre (250 µm)
3. Micro-Bundle with 12 fibres
4. Reinforced watertight glass yarns
5. Outer sheath in LSZH material with UV resistant additive

Characteristics

- Micro-Bundle design for easy installation
- Indoor cable for horizontal and vertical installations
- Flame retardant (IEC 60332-1 & NFC 32070 C2)
- Fire retardant (IEC 60332-3 & NFC 32070 C1)
- Outdoor cable for installation in a duct by pulling
- Waterproof structure, rodent resistant and UV-resistant
- All dielectric design
- Designed for termination by splicing
- 12 fibres per Micro-Bundle
- Smoke Density (IEC61034)
- Reaction fo fire: Cca a1d0s1 according to EN50575:2014 +A1:2016
- Sheath Color: Aqua (OM3), Yellow (OS2)

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

LANmark-OF Micro-Bundle Universal (144F) Cca

CHARACTERISTICS

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

Product list

	Aginode ref.	Country ref.	Name
	N164.MBUN144-YC	-	LANmark-OF Micro-Bundle Universal 144x Singlemode 9/125 OS2 LSZH Cca s1ad0a1 Yellow

= Make to order, = In Stock

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.