LANmark-OF MPO-MPO 跳线 LSZH

- 安捷诺 MPO 跳线采用纤细线缆设计，外径仅为 3mm，为数据中心用户的面板前线缆管理提供了 19% 的空间。
- 12芯光缆
- 安捷诺 MPO 连接器的光学性能优于行业水平，符合国际标准。
- 可用于单模和对弯曲不敏感的 OM3/OM4/OM5
- LSZH阻燃类型
- 直通极性（B 型）符合 TIA 568.C.3 标准， 键上/键上方向
- 两端均为母头 MPO 连接器



STANDARDS

ANSI/TIA-568-C.3
ISO/IEC 11801

应用

安捷诺 MPO 跳线专为支持 40G、100G、200G 和 400G 等数据中心高速网络应用而设计。安捷诺的低损耗光学性能可支持至少 6 个 MPO 连接，以便在超大型数据中心中使用中间分配器。MPO 光缆针对外径进行了优化，并保持良好的拉力和挤压性能。每条 MPO 干线出厂时都附有测试报告，以确保性能。

MPO 连接器符合 IEC 61754-7-1 和 GR-1435-CORE 标准

多模 MPO 连接器为 PC 型，单模 MPO 连接器为 APC 型

电缆采用 LSZH 材料，符合 IEC 60332-1&IEC 50332-3-24、IEC 61034-2和 IEC 60754-1&2标准

光纤符合 IEC 60793-2-10（A1a.2b OM3 和 A1a.3b OM4）、IEC 60793-2-50（B6_a1）和 ITU-T G.657.A1 单模标准。

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

LANmark-OF MPO-MPO 跳线 LSZH

CHARACTERISTICS

结构特性	
光纤类型	OM4 50/125
传输特性	
最大插入损耗，dB	0.25 dB

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

Product list

	Aginode ref.	Country ref.	Name
	N125.7SUV2	-	LANmark-OF MPO-MPO 跳线，OM4，直连，MPO 母头-MPO 母头，12芯，LSZH，紫色，超低损耗，2米
	N125.7SLV2	-	LANmark-OF MPO-MPO 跳线, OM4, 直连型, MPO 母头-MPO 母头, 12芯, LSZH,紫色, 低损耗, 2米
	N125.4SLY2	-	LANmark-OF MPO-MPO 跳线，OS2 APC，G.657.A1，直连，MPO 母头-MPO 母头，12芯，LSZH，黄色，低损耗，2米
	N125.5SLA2	-	LANmark-OF MPO-MPO 跳线，OM3，直连，MPO 母头-MPO 母头，12芯，LSZH，水绿色，低损耗，2米

= Make to order, = In Stock

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.