

LANmark 区域分配盒

- 用作集合点
- 与所有 LANmark 快插连接器兼容。
- 6 或 12 个带快门的编号快插端口。
- 易于安装

区域分配盒设计用作合并点，大大提高了开放式办公环境中办公桌位置的灵活性。在需要频繁移动工作区插座的办公室，它们尤其有用。

Aginode 区域分配盒具有多种安装特性，易于安装在墙壁、高架地板下或天花板空隙中。

它们与所有 LANmark 卡入式连接器兼容，只需 "一击" 即可轻松插入。



LANmark 区域分配盒

CHARACTERISTICS

结构特性

颜色	白 RAL 9002
材料	钢

尺寸特性

深度	200 mm
高度	45 mm
宽度	230 mm

使用特性

端口数	12
-----	----

Resources

安装指南



PDF - 1.18 MB
OF 强化可锁区域配电箱
下载 

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

Product list

	Aginode ref.	Country ref.	Name	颜色	深度	高度	宽度
	N521.600	-	LANmark ZD box 12 Snap-In White	白 RAL 9002	200 (mm)	45 (mm)	230 (mm)
	N521.606	-	LANmark ZD box 6 Snap-In White	白 RAL 9002	125 (mm)	42 (mm)	120 (mm)
	N521.612	-	LANmark Ruggedised Lockable ZD Box White	白 RAL 9002	300 (mm)	55 (mm)	260 (mm)
	N521.6121	-	LANmark Ruggedised Lockable ZD Box Foot White	白 RAL 9002	250 (mm)	35 (mm)	253 (mm)
☎ = Make to order,  = In Stock							

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.