

WLB-Max : Indoor Wall Box

The WLB box range is designed to manage the infrastructure of passive solutions, ensuring efficient management of fibers and connections in network environments. It provides optimized cable organization, ensuring reliable and secure deployment.

Description

The WLB-Max is a compact and efficient fiber management solution designed for passive infrastructure cabling and other indoor fiber networks. It ensures secure connectivity, high-density fiber management, and easy maintenance.

Key Features

- **Modular Design:** Designed for easy integration in LAN environments.
- **High-Capacity Termination:** Supports up to up to 26 SC adapters.
- **Secure Access:** 8 mm triangular key locking system.
- **Quick Installation & Maintenance:** Tool-free door dismantling and front-access patching.
- **Robust Build:** Designed for reliable long-term indoor operation.

Applications

- Passive fiber optic infrastructure networks(GPON & P2P, FTTO...cet)
- Wall-mounted **fiber distribution point** for structured cabling

Disponible Version

- **Standard :** Comes with SC/APC adapters, ready for custom configurations.



STANDARDS

Aginode specification

WLB-Max : Indoor Wall Box

CHARACTERISTICS

结构特性

电缆引入线	从左侧
颜色	浅灰 RAL 7035
材料	聚碳酸酯

尺寸特性

深度	150 mm
高度	100 mm
连接器数	26
宽度	450 mm

使用特性

适配器	SC/APC
Locking system	Triangle
最小弯曲半径 - 静态	15 mm
操作温度, 范围	-25...70 °C
包装	箱

Product list

Aginode ref.	Country ref.	Name	材料	连接器数
NWLB.X026DU.W	-	WLB-Max - Standard	聚碳酸酯	26

☎ = Make to order, 📦 = In Stock

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.