

LANmark-OF UC PE (单元管钢装甲)

UC 光纤电缆

- 室外管道或直接埋设
- 波纹钢带铠装
- 适用于所有光纤等级
- 提供全面的防鼠保护

说明和应用


这种结构适用于室外管道和直接埋设。它由波纹钢带铠装组成，提供全面的防鼠保护。铠装周围是玻璃纱。电缆外层为高密度聚乙烯。

松套管设计最多可容纳 24 根纤维，纤维直径为 250 微米。这些纤维的端接采用尾纤拼接方式。

松散管中的凝胶和防水玻璃纱确保了电缆的防水性。

特点

- 室外电缆，可安装在管道中或直接埋入地下
- 设计用于拼接端接
- 中央松散管设计
- 波纹钢保护
- 防水结构、防鼠、防紫外线
- 提供所有光纤等级
- 可提供 4-24 纤维



STANDARDS

ISO/IEC 11801

LANmark-OF UC PE (单元管钢装甲)

CHARACTERISTICS

结构特性

结构类型

松套管



光纤类型

SM (G657.A1)

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

Product list

Aginode ref.	Country ref.	Name
N164.UCPE06B	-	LANmark-OF UC 6x Singlemode 9/125 OS2 PE Black
N164.UCPE12B	-	LANmark-OF UC 12x Singlemode 9/125 OS2 PE Black
N164.UCPE24B	-	LANmark-OF UC 24x Singlemode 9/125 OS2 PE Black
N165.UCPE06B	-	LANmark-OF UC 6x Multimode 50/125 OM3 PE Black
N165.UCPE12B	-	LANmark-OF UC 12x Multimode 50/125 OM3 PE Black
N165.UCPE24B	-	LANmark-OF UC 24x Multimode 50/125 OM3 PE Black
N167.UCPE06B	-	LANmark-OF UC 6x Multimode 50/125 OM4 PE Black
N167.UCPE24B	-	LANmark-OF UC 24x Multimode 50/125 OM4 PE Black
N167.UCPE12B	-	LANmark-OF UC 12x Multimode 50/125 OM3 PE Black

 = Make to order,  = In Stock

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.