

Essential-6数据铜缆

- 符合所有 6 类电缆标准
- 支持 E 级应用
- 十字骨架帮助保证线缆的结构和性能稳定
- 23AWG 导线规格

应用

Aginode Essential-6 电缆按照最新的六类规格制造和测试。它们与完整的 Essential-6 模块化和 PCB 连接系列产品兼容。当电缆与 Essential-6 插座和配线架一起安装时，可从 Aginode 网站获得 25 年 E 级链接证书。

性能

Aginode Essential-6 电缆符合国际、欧洲和美国电缆标准的要求，包括 ISO/IEC 11801、IEC 61156-5、EN 50173、EN 50288 和 TIA/EIA 568-C.2。

安装

为支持正确设置手持式分析仪进行安装测试，电缆打印图例中给出了实际电缆 NVP 值。



STANDARDS

ANSI/TIA-568-C.2
ISO/IEC 11801

Essential-6数据铜缆

CHARACTERISTICS

结构特性

外护套	聚氯乙烯
电缆类型	U/UTP

机械特性

最大操作抗拉强度	100 N
----------	-------

使用特性

范围	essential-6
----	-------------

Resources

文件

Freetable Ess6 channel.xls xls — 14 KB 下载 ↴

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.



Product list

Aginode ref.	Country ref.	Name	外护套	电缆类型
 N100.166	-	Essential-6 U U/UTP Cat 6 PVC 24AWG 305m /箱	聚氯乙烯	U/UTP
 N100.161	-	Essential-6 U/UTP Cat 6 LSZH 24AWG 305m /箱	低烟无卤	U/UTP
 N100.170	-	Essential-6 U/UTP Cat 6 LSZH 23AWG 305m 箱装	低烟无卤	U/UTP
 N100.175	-	Essential-6 U/UTP AWG23 Cat 6 PVC 灰色 305m/箱	聚氯乙烯	U/UTP
 N100.170-GB1-D	-	Essential-6 U/UTP Cat 6 PVC 23AWG 305m reel in box	低烟无卤	U/UTP
N100.170-GB1-D	-	Essential-6 U/UTP AWG23 CAT 6 LSZH GB 31247 B1 (d0,t0,a1) 深灰色 305M/Reel	低烟无卤	UTP

 = Make to order,  = In Stock

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.