GG45 8C PCB jack

- Right angled Cat 7A PCB jack up to 1500 MHz
- to be used in active equipment or patch panels
- UL94-V0 plastic components
- RoHS compliant
- Wave solder compatible.

Please refer to the datasheet of N420.738 for more detailed information and performance tables.





STANDARDS

ISO/IEC 11801

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

GG45 8C PCB jack

CHARACTERISTICS

结构特性	
颜色	黑
屏蔽	是
连接器类型	母头
尺寸特性	
深度	21.84 mm
高度	13.5 mm
宽度	15.24 mm
使用特性	
范围	LANmark-7A
类型	Cat. 7A
部件功能	连接器

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

Product list

	Aginode ref.	Country ref.	Name	范围	类型
	N420.738	-	GG45 Right angle 8 contact jack for PCB mount	LANmark-7A	Cat. 7A

= Make to order, = In Stock

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.