SNAP-IN模块化配线架

24口角形配线架（SNAP-IN，黑色）

Aginode Ref: N521.671

- 支持高密度配线——非常适合数据中心，无需额外进行线缆管理
- 兼容所有Snap-In连接器
- 配备独有的自动连接接地系统
- 通用设计支持无屏蔽和屏蔽连接器
- 另有白色款可选



STANDARDS

Manufacturer specification

Aginode Snap-In 系列配线架专为兼容 LANmark 产品系列中的任何 Snap-In 连接器而设计（包括 LANmark-7A、LANmark-7、LANmark-6A、LANmark-6 和 LANmark-5）。

Snap-In 配线架采用专有的 Clip-On 系统，可将连接器牢固固定在配线架上，并提供一种简便的方法将屏蔽连接器接地，从而简化安装过程。配线架与地线的连接通过独特的 Auto-Connect 功能实现，无需单独的接地导线。

此外，该系列配线架还配有一系列配套的线缆管理产品，例如空白面板和跳线导轨。

这些配线架专为标准 19 英寸机柜设计，高度为 1U，并具备以下特点：

- 提升的跳线密度
- 24个带防尘盖的空闲端口，42 HU机柜内最多可容纳912个端口
- 可与开放式机架框架或封闭/开放式机柜配合使用，实现垂直布线管理
- 采用印刷编号系统作为端口标识
- 包含后部线缆管理支持
- 专为屏蔽和非屏蔽 Snap-In 连接器设计
- 采用卡扣式结构，为屏蔽连接器提供快速且安全的接地

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

24口角形配线架（Snap-in，黑色）

Characteristics

结构特性	
颜色	黑
材料	钢
尺寸特性	
深度	120 mm
高度单位	1 U
宽度	19 inches
使用特性	
应用类型	固定安装
机械耐受度	良好的机械防护
端口数	24
包装	箱
抗振	高

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.