# LANsense Fibre Patch Cords

**LC DUPLEX LANSENSE PATCH CORD - OS2**



**Aginode Ref:** N884.4LLY2

- Additional copper pin for port detection
- High bandwidth OS2 fibre
- Available with LC connectors

The LC LANSense patch cord uses the standard LC duplex connector, enabling high-density fiber connections to be achieved. The LC LANSense cord, however, has an over-boot to incorporate the sensing capability of the LANSense products. The LANSense patch cords are available in both high bandwidth OM4 and single-mode OS2 fibre types and so offer a comprehensive range of patch cords for interfacing with the latest network equipment.

## STANDARDS

ISO/IEC 11801

*All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.*

# LC Duplex LANsense Patch Cord - OS2

## Characteristics

| | |
|---|---|
| **结构特性** | |
| 颜色 | 黄 |
| 光纤类型 | OS2 |
| 连接器类型 | LC |
| **使用特性** | |
| 长度 | 2 m |
| 部件功能 | 跳线 |

*All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.*