LANmark 工业 IP65/67 插座

LANMARK INDUSTRY IP65/67 OUTLET KIT 2 SNAP-IN CATEGORY 7A BLACK

Aginode Ref: N42i.003

- Industrial outlet with 2 connectors LANmark-7A GG45 shielded
- IP65/67 Protection level (Dust/Liquids)
- Easy termination, without punch down tool.
- Full conformity with the physical and mechanical requirements of the ISO/IEC 24702
- Conform with IEC61073-3-106 (8way Industrial connector)
- 2 connectors LANmark-7A GG45 shielded included



STANDARDS

ISO/IEC 11801
ISO/IEC 24702

Application

The LANmark Industry IP65/67 outlet is designed to enable the installation of LANmark-7A Snap-in connectors in industrial and harsh areas. It is conceived for wall mount installation with cable penetration from below or above. The IP65/67 outlet can be used in structured industrial cabling and as interface with the production islands.

Performance

The LANmark-7A Snap-in connector has been designed to reach the highest performance in Category 7A and Class FA. It has outstanding performance for attenuation (insertion loss), NEXT/FEXT, Power Sum NEXT/FEXT and Return Loss exceeding the Cat 7A connector specs as in ISO/IEC 11801:2011. Used with Aginode LANmark Industry cables and patchcords, the connector is independantly tested to exceed the link and stringent four-connector channel requirements as defined in the ISO/IEC11801:2011. As such it supports all data applications defined for Cat 5e, Cat 6, Cat 6A and Cat 7A, such as:

- 10baseT
- Fast Ethernet
- Gigabit Ethernet
- 10G-Base-T
- 155 ATM
- 622 ATM,
- 1.2 ATM
- Industrial Ethernet

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

Guarantees

The LANmark-7A Snap-in connector is covered by the guarantee as in The General Terms and Conditions of Sales.

Installation

The LANmark-7A Snap-in connectors are designed for an easy and rapid termination. Fitting them inside the IP65/67 outlet is a straight forward operation.

- Fast termination of cable
- Colour code : TSB568A & TSB568B
- Can be used with all types of cables : F^2TP, UTP, SF/UTP or STP
- Accepts 24, 23 and 22 AWG cable, PUR, LSZH
- For all LANmark Industry cables

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

LANmark Industry IP65/67 outlet kit 2 Snap-In Category 7A black

Characteristics

结构特性	
颜色	黑
屏蔽	是
电缆引入线	从顶部或底部
材料	聚碳酸酯
连接器类型	RJ 45
尺寸特性	
深度	69 mm
高度	173 mm
螺杆数	4
宽度	90 mm
螺杆尺寸	4.00mm
电缆数	2
壁厚	2.5 mm
单位近似重量	0.29 kg
Length cable end on inner side	230.0 mm
电气特性	
最大工作频率	1000 MHz
特性阻抗	100 Ohm
机械特性	
机械耐冲击性能	一般工业环境下使用
使用特性	
抗电磁干扰	Yes
应用类型	工业安装
端口数	2
耐气候性	优异

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

类型	Cat. 7A
部件功能	布线和连接解决方案
包装	箱
最高工作温度	70 °C
最低工作温度	-40 °C
防水	IP 65/67

文件

Freetable LM7A Channel.xls xls — 19 KB　下载

销售和交付信息

Includes automatic shutters, 2xCable Glands, 2xLANmark-7A shielded connector, 1xLabelling window. Colour: Black RAL9011

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.