

240 系统

FIBREROUTE 240MM(9.45 INCH) CHANNEL COVER

Aginode Ref: N350.240FC10P

Aginode Fibre Trunking System provides a dedicated pathway for fibre optic cables and cords to protect them from accidental damage. The system offers a flexible, high-capacity solution for data centre containment which is easy to install and reconfigure to meet future needs.

- Pathway system designed for accommodation of Data Center fibre cables
- Cover for 240mm(9.45 inch) width channel
- Tough, flame retardant PVC material

The Aginode Fibre Trunking System provides a dedicated pathway through data centre spaces and IT facilities for routing fibre cables.

The rigid channel with matching cover protects fibre optic cables from damage.

All components of the system are made of tough, fire retardant materials.

The system components have a smooth inner surface to ensure a safe path for fibre optic cables and feature internal radius management to facilitate the maintenance of bend radii for cables and patch cords.

The Cover for the 240mm(9.45 inch) Channel provides protection to fibre cables and cords from dust and falling items.

All components of the system including the covers can be installed and uninstalled without special tools.

Size:

Depth 12mm(0.47")



STANDARDS

EN 50173-5
ISO/IEC 24764
UL 94 V0

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

Length 2000mm(78.7")

Width 274mm(10.8")

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

FIBREROUTE 240mm(9.45 inch) Channel Cover

Characteristics

结构特性

颜色	黄
材料	聚氯乙烯

尺寸特性

深度	12 mm
近似重量	1 kg/m
宽度	274 mm
长度	2000 mm

使用特性

操作温度, 范围	-25...60 °C
存储温度范围	-45...60 °C