

光纤槽道240mm系统

FIBREROUTE 240MM(9.45 INCH) EQUAL TEE

Aginode Ref: N350.240FA02A

Aginode Fibre Trunking System provides a dedicated pathway for fibre optic cables and cords to protect them from accidental damage. The system offers a flexible, high-capacity solution for data centre containment which is easy to install and reconfigure to meet future needs.

- Pathway system designed for accommodation of data centre fibre cables
- Free of sharp edges
- Quick connect system with a wide range of fixtures and fittings
- High capacity pathway accommodating large volumes of cables with space for future expansion
- Equal Tee to provide branch connections in 360mm systems
- Tough, flame retardant ABS material

The Aginode Fibre Trunking System provides a dedicated pathway through data centre spaces and IT facilities for routing fibre cables.

The rigid channel with matching cover protects fibre optic cables from damage.

All components of the system are made of tough, fire retardant materials.

The system components have a smooth inner surface to ensure a safe path for fibre optic cables and feature internal radius management to facilitate the maintenance of bend radii for cables and patch cords.

The Equal Tee is used to create branches in 240mm channels. This form of interconnection is widely adopted in data centre designs compliant to ISO/IEC 11801-5, EN 50173-5 or EN 50600-2-4 within an MD pathway to create connections between rows or rooms.

All components of the system including the covers can be installed and uninstalled without special tools.



STANDARDS

EN 50173-5
ISO/IEC 24764
UL 94 V0

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

Size:

Depth 117mm(4.6")

Length 470mm(18.5")

Width 377mm(14.8")

FIBREROUTE 240mm(9.45 inch) Equal Tee

Characteristics

结构特性

颜色	黄
材料	ABS

尺寸特性

深度	117 mm
宽度	377 mm
长度	470 mm
近似净重量	1.0 kg

使用特性

操作温度，范围	-25...60 °C
存储温度范围	-45...60 °C