出线组件及固定件

FIBREROUTE WATERFALL ASSEMBLY-130MM(5.1 INCH)

Aginode Ref: N350.003SD02A

Aginode Fibre Trunking System provides a dedicated pathway for fibre optic cables and cords to protect them from accidental damage. The system offers a flexible, high-capacity solution for data centre containment which is easy to install and reconfigure to meet future needs.



- Pathway system designed for accommodation of data centre fibre cables
- Free of sharp edges
- Quick connect system with a wide range of fixtures and fittings
- High capacity pathway accommodating large volumes of cables with space for future expansion
- Waterfall Assembly to provide transition from Channel to racks or cabinets
- 130mm(5.1 inch) Waterfall could attach 2 flex tube(N350.003SD10A)
- Tough, flame retardant ABS material

STANDARDS

EN 50173-5
ISO/IEC 24764
UL 94 V0

The Aginode Fibre Trunking System provides a dedicated pathway through data centre spaces and IT facilities for routing fibre cables .
The rigid channel with matching cover protects fibre optic cables from damage.
All components of the system are made of tough, fire retardant materials.
The system components have a smooth inner surface to ensure a safe path for fibre optic cables and feature internal radius management to facilitate the maintenance of bend radii for cables and patch cords.

The Waterfall Assembly provides an exit for fibre optic cables or cords from the channel into racks or cabinets. The split plastic flex tube is attached to the Waterfall for easy access to the fibre optic cables.

The Waterfall is secured to the channel using T-type screws.

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

FIBREROUTE Waterfall Assembly-130mm(5.1 inch)

Characteristics

结构特性	
颜色	黄
材料	ABS
尺寸特性	
近似净重量	0.3 kg
使用特性	
操作温度，范围	-25...60 °C
存储温度范围	-45...60 °C

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.