# LANmark-6A Cable

**LANMARK-6A F/FTP AWG23 CAT 6A LSZH DCA S2 D1 A1 ORANGE 1000M REEL**



**Aginode Ref:** N100.692G-OD

- Ideal cable for 10GBase-T application
- Full compliance to latest standards for Category 6A and Class EA
- Guaranteed performance up to 500MHz
- Individual pair shielding offering Alien Crosstalk immunity

## Application

LANmark-6A cables are the ideal solution for a 10G Ethernet network. The range has been designed specifically to support the higher frequencies required for 10 Gigabit Ethernet, while maintaining full backwards compatibility with today's needs. All LANmark-6A cables are shielded, in order to ensure immunity to Alien Crosstalk and other external interferences.

- 10Base-T Ethernet
- 100Base-TX Fast Ethernet
- 1000Base-TX Gigabit Ethernet
- 10GBase-T 10 Gigabit Ethernet IEEE 802.3
- 155 Mbit ATM
- 1.2 Gbit ATM
- future Cat 6A and Class EA applications
- PoE++ Type 4 (IEEE 802.3bt)

## Performance

With guaranteed performance to 500MHz, Aginode LANmark-6A cables exceed the requirements of the International, European and American cable standards, including ISO/IEC 11801, IEC 61156-5, EN 50173, EN 50288 and TIA/EIA 568.2-D

When used in combination with Aginode LANmark-6A connectors and LANmark-6A Ultim patch cords, the system supports the 10GBase-T applications as defined in IEEE 802.3an and meets or exceeds the link and channel requirements for Category 6A and Class EA as defined in TIA/EIA 568.2-D and ISO/IEC 11801.

## STANDARDS

ANSI/TIA 568.2-D
EN 50173-1
EN 50288-4-1
IEC 61156-5
IEEE 802.3bt (PoE++)
ISO/IEC 11801

*All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.*

# Installation

To support the correct set-up of hand held analysers for installation testing, the actual cable NVP value is given in the cable's print legend.

# Guarantees

Traceability codes on both cable and packaging ensure quality validation of the installed cable.

Installations with LANmark-6A cable and connectivity are qualified for a 25 year full system warranty, which includes Parts, Channel Performance, Application Support and Labour, as described in the Aginode Certified System Warranty.

## Electrical Performance LANmark-6A FFTP Cable

| Freq | Attn | | NEXT | | PSNEXT | | ACR-F | | PS ACR-F | | PS ANEXT | | PS AACR-F | | RL | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | in dB | | in dB | | in dB | | in dB | | in dB | | in dB | | in dB | | in dB | |
| in MHz | Max. | Typ. | Min. | Typ. | Min. | Typ. | Min. | Typ. | Min. | Typ. | Min. | Typ. | Min. | Typ. | Min. | Typ. |
| **1** | 2,1 | 2,1 | 74,3 | 104,3 | 72,3 | 102,3 | 67,8 | 92,8 | 64,8 | 89,8 | 67,0 | 90,0 | 67,0 | 76,7 | 20,0 | 26,0 |
| **4** | 3,8 | 3,8 | 65,3 | 95,3 | 63,3 | 93,3 | 55,8 | 80,8 | 52,8 | 77,8 | 67,0 | 90,0 | 66,2 | 75,9 | 23,0 | 29,0 |
| **10** | 5,9 | 5,9 | 59,3 | 89,3 | 57,3 | 87,3 | 47,8 | 72,8 | 44,8 | 69,8 | 67,0 | 87,0 | 58,2 | 67,9 | 25,0 | 31,0 |
| **16** | 7,5 | 7,5 | 56,2 | 86,2 | 54,2 | 84,2 | 43,7 | 68,7 | 40,7 | 65,7 | 67,0 | 85,0 | 54,1 | 63,8 | 25,0 | 31,0 |
| **20** | 8,4 | 8,4 | 54,8 | 84,8 | 52,8 | 82,8 | 41,8 | 66,8 | 38,8 | 63,8 | 67,0 | 84,0 | 52,2 | 61,9 | 25,0 | 31,0 |
| **31,25** | 10,5 | 10,5 | 51,9 | 81,9 | 49,9 | 79,9 | 37,9 | 62,9 | 34,9 | 59,9 | 67,0 | 82,1 | 48,3 | 58,0 | 23,6 | 29,6 |
| **62,5** | 15,0 | 15,0 | 47,4 | 77,4 | 45,4 | 75,4 | 31,9 | 56,9 | 28,9 | 53,9 | 65,6 | 79,0 | 42,3 | 52,0 | 21,5 | 27,5 |
| **100** | 19,1 | 19,1 | 44,3 | 74,3 | 42,3 | 72,3 | 27,8 | 52,8 | 24,8 | 49,8 | 62,5 | 77,0 | 38,2 | 47,9 | 20,1 | 26,1 |
| **155** | 24,1 | 24,1 | 41,4 | 71,4 | 39,4 | 69,4 | 24,0 | 49,0 | 21,0 | 46,0 | 59,6 | 74,1 | 34,4 | 44,1 | 18,8 | 24,8 |
| **200** | 27,6 | 27,6 | 39,8 | 69,8 | 37,8 | 67,8 | 21,8 | 46,8 | 18,8 | 43,8 | 58,0 | 72,5 | 32,2 | 41,9 | 18,0 | 24,0 |
| **250** | 31,1 | 31,1 | 38,3 | 68,3 | 36,3 | 66,3 | 19,8 | 44,8 | 16,8 | 41,8 | 56,5 | 71,0 | 30,2 | 39,9 | 17,3 | 23,3 |
| **300** | 34,3 | 34,3 | 37,1 | 67,1 | 35,1 | 65,1 | 18,3 | 43,3 | 15,3 | 40,3 | 55,3 | 69,8 | 28,7 | 38,4 | 16,8 | 22,8 |
| **500** | 45,3 | 45,3 | 33,8 | 63,8 | 31,8 | 61,8 | 13,8 | 38,8 | 10,8 | 35,8 | 52,0 | 66,5 | 24,2 | 33,9 | 15,2 | 21,2 |

*All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.*

# LANmark-6A F/FTP AWG23 Cat 6A LSZH Dca s2 d1 a1 Orange 1000m reel

## Characteristics

| | |
|---|---|
| **结构特性** | |
| 颜色 | 橙 |
| 外护套 | 低烟无卤 |
| 电缆类型 | F/FTP |
| **尺寸特性** | |
| 近似重量 | 49 kg/km |
| 导体横截面尺寸（AWG） | 23 |
| 绝缘外径 | 1.36 mm |
| 标称外径 | 7.0 mm |
| **电气特性** | |
| 互电容 | 45 nF/km |
| 特性阻抗 | 100 Ohm |
| 最大转移阻抗在30MHz | 120 Ohm/km |
| 20°C时导体的最大直流电阻 | 80 Ohm/km |
| **机械特性** | |
| 最大操作抗拉强度 | 100 N |
| **传输特性** | |
| 时延值 | 30 ns/100m |
| 传播速度 | 82 % |
| 耦合衰减在30MHz | >85 dB |
| 传播延迟值，最大100MHz | 536 ns/100m |
| **使用特性** | |
| 范围 | LANmark-6A |
| 气体腐蚀性 | IEC 60754-1; IEC 60754-2 |
| 长度 | 1000 m |
| 操作温度，范围 | -20...60 °C |

*All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.*

| | |
|---|---|
| 类型 | Cat. 6A |
| 阻燃 - 火焰 | IEC 60332-1 |
| 烟密度 | IEC 61034 |
| 包装 | 电缆盘 |
| 环境安装温度，范围 | -10...60 °C |
| 最小弯曲半径 - 安装 | 56 mm |
| 最小弯曲半径 - 工作 | 28 mm |

## 文件

Freetable LM6A FFTP V3.xls xls — 25.5 KB 下载

## 业绩声明

LANmark-6A F/FTP AWG23 Cat 6A LSZH Dca s2 d1 a1 Orange 1000m reel pdf — 141.21 KB 下载

*All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.*