

Distribution - Unibundle cable Cca

UB LSZH 6XSM G657A2 SP1879 BK

Aginode Ref: 10537713

Unibundle cable up to 12 fibres

This unibundle cable is designed for indoor/outdoor installation.

This cable has an outstanding fire behaviour.

Access to the tube is made easy with the internal ripcord.

This cable can be operated under a large temperature range.

Design

The UB LSZH* SP1879 cable has a central bundle with 6 fibres inside. The design is reinforced by a layer of watertight glass yarns and a LSZH* sheath.

Fibre type

The UB LSZH* SP1879 cable is available with multimode and singlemode fibres.


Technical performances

The unibundle cable performances are specified in the following tables.

Additional details

This cable is provided with a black sheath, other sheath colours are also available. Long exposure to UV with these other colours could generate colour fading.

* LSZH: Low Smoke Zero Halogen.



STANDARDS

EN 50399 B2

IEC 60332-1

IEC 60332-3

IEC 60754-1

IEC 60794

IEC 61034

NF C32-070/C2

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

UB LSZH 6xSM G657A2 SP1879 BK

Characteristics

结构特性

颜色	黑
光纤类型	SM (G657.A2)
外护套	低烟无卤
无卤	IEC 60754-1
长度水密封性所用材料	Watertight glass yarns
不含金属	Yes
结构类型	单束管
额外加强件	玻璃纱

尺寸特性

近似重量	45 kg/km
光纤数	6
光纤数, 范围	...
标称外径	6.0 mm

机械特性

机械耐冲击性能	10次冲击/ 3N.M
最大长期拉力负载	0.7 kN
耐挤压 (IEC 794-1-E3)	200 N/cm
最大安装拉力	2200 N

使用特性

操作温度, 范围	-40...60 °C
阻燃	IEC 60332-3
最小弯曲半径 - 静态	60 mm
阻燃 - 火焰	IEC 60332-1
烟密度	IEC 61034-2
抗UV	非常好
存储温度范围	-40...60 °C
敷设操作弯曲半径	60 mm

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

安装类型

室内/户外

Installation temperature, range

0..40 °C

防水

纵向和径向

业绩声明

UB LSZH 6xSM G657A2 SP1879 BK pdf — 119.99 KB 下载 ↓

销售和交付信息

Standard Marking

Aginode - FIBRE OPTIC CABLE - UB LSZH Cca s1a d1 a1 SP1879 - XXxYY - FB - TN - metric

XX = Fibre Count YY = Fibre Type FB = Frameries, Belgium (manufacturing place) TN = Traceability Number