

LANmark-7 Cable

LANMARK-7 S/FTP AWG23 CAT 7 LSZH B2CA S1A D1 A1 ORANGE 1000M REEL

Aginode Ref: N100.365-OB

- S/FTP cable with individually shielded pairs and global braid
- Exceeds Category 7 ACR with >30dB
- Optimised for use with LANmark-7A GG45 connector
- Easy to install
- Enhanced reaction-to-fire performance according to CPR classification B2ca-s1a,d1,a1 (h/EN50575:2014+A1:2016)

Description

LANmark-7 cable has an S/FTP construction with individual pair foils and an overall braid offering superior performance in terms of ACR. It is fully compliant with the Category 7 standards and when installed together with the GG45 LANmark-7A connector, the system is guaranteed to exceed all channel requirements in all configuration scenarios (up to 4-connector channels).

Application

LANmark-7 will support all current and planned data applications developed for cabling up to Class F.

- All Ethernet applications including
- 1000Base-T
- 1000Base-TX
- 10GBase-T
- CATV up to 862MHz
- Any future Class F application

Installation

Ease of Installation is one of the unique features of LANmark-7 cable. Extra attention has been paid to ensure screen coverage is maintained both during and after installation. The cable has been designed specifically to offer both optimum performance and ease of termination when used in conjunction with the LANmark-7A GG45 connector.

To support the correct set-up of hand held analysers for installation testing, the actual cable NVP value is given in the



STANDARDS

EN 50173-1
EN 50288-4-1
IEC 60332-3-24
IEC 61156-5
IEEE 802.3bt (PoE++)
ISO/IEC 11801

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

cable's print legend.

Electrical Performance LANmark-7 Cable

Frequency (MHz)	Attenuation (dB/100m)		NEXT (in dB)		ACR (in dB)		PS-NEXT (in dB)		ACR-F (in dB)		PS-ACR-F (in dB)		Return Loss (in dB)	
	Max	Typ	Min	Typ	Min	Typ	Min	Typ	Min	Typ	Min	Typ	Min	Typ
1.00	4.0	1.8	75.0	100.0	71.0	98.2	72.0	98.0	75.0	98.0	75.0	96.0	20.0	20.0
4.00	4.0	3.5	75.0	100.0	71.0	96.5	72.0	96.0	75.0	96.0	75.0	96.0	23.0	20.0
10.00	5.9	5.5	75.0	100.0	69.1	94.5	72.0	96.0	75.0	96.0	72.3	96.0	25.0	28.0
16.00	7.4	6.8	75.0	100.0	67.6	93.2	72.0	96.0	71.2	96.0	68.2	94.0	25.0	28.0
20.00	8.3	7.7	75.0	100.0	66.7	92.3	72.0	96.0	69.3	94.0	66.3	92.0	25.0	28.0
31.25	10.4	9.6	75.0	100.0	64.5	90.4	72.0	96.0	65.4	90.0	62.4	88.0	23.0	26.0
62.50	14.9	14.0	75.0	100.0	60.1	86.0	72.0	96.0	59.4	84.0	56.4	82.0	21.5	25.0
100.00	19.0	17.7	72.4	100.0	53.4	82.3	69.4	96.0	55.3	75.0	52.3	73.0	20.1	24.0
155.00	24.0	22.8	69.5	96.0	45.6	73.2	66.5	93.0	51.5	70.0	48.5	68.0	18.8	23.0
250.00	31.0	29.0	66.4	94.0	35.5	65.0	63.4	91.0	47.3	66.0	44.3	64.0	17.3	22.0
300.00	34.2	32.1	65.2	92.0	31.1	59.9	62.2	88.0	45.8	64.0	42.8	62.0	17.3	20.0
600.00	50.1	45.5	60.7	90.0	10.6	44.5	57.7	86.0	39.7	64.0	36.7	62.0	17.3	20.0

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

LANmark-7 S/FTP AWG23 Cat 7 LSZH B2ca s1a d1 a1 Orange 1000m reel

Characteristics

结构特性

屏蔽	铝箔+镀锡铜编织
外护套	低烟无卤
护套颜色	橙
无铅	Yes
电缆类型	S/FTP
加蔽线	无

尺寸特性

近似重量	50 kg/km
线对数	4
导体横截面尺寸 (AWG)	23
绝缘外径	1.42 mm
标称外径	7.6 mm

电气特性

互电容	45 nF/km
特性阻抗	100 Ohm
最大转移阻抗在30MHz	50 Ohm/km
20°C时导体的最大直流电阻	80 Ohm/km

机械特性

最大操作抗拉强度	100 N
----------	-------

传输特性

时延值	25 ns/100m
传播速度	82 %
耦合衰减在30MHz	>85 dB
传播延迟值, 最大100MHz	536 ns/100m

使用特性

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

范围	LANmark-7
气体腐蚀性	IEC 60754-1; IEC 60754-2
长度	1000 m
操作温度, 范围	-20...60 °C
阻燃	IEC 60332-3-24 (cat C)
类型	Cat. 7
阻燃 - 火焰	IEC 60332-1
烟密度	IEC 61034-2
包装	电缆盘
环境安装温度, 范围	-10...60 °C
最小弯曲半径 - 安装	61 mm
最小弯曲半径 - 工作	31 mm

文件

Freetable LM7 600_3.xls xls — 19 KB [下载](#) ↓

业绩声明

LANmark-7 S/FTP AWG23 Cat 7 LSZH B2ca s1a d1 a1 Orange 1000m reel pdf — 141.41 KB [下载](#) ↓