

Splicing Patching / COSH48

COSH48 SC 2U LEFT AXIS VERSION

Aginode Ref: 10231604

- Elementary module
- Left axis version
- Lateral spool for jumper management
- Pre-connectorised with 48 pigtailed and 48 SC

Application

On the terminal part of the FTTH network, the COSH 48 modules receive the fibres located downstream the mutualisation point.

Details

The COSH 48 2U module includes a space reserved for splicing of the incoming fibres. Splicing is performed in splicing trays.

A front panel ensures the patching function with a capacity of 48 SC adaptors.


The module is compatible with all types of frames (19" or ETSI standards) with a minimum depth 300mm. It is available both in elementary and subrack versions.

The accessories fitted with the module guarantee the conformity with the bending radius of the fibre (G652). It is prepared in order to minimise the installation time on sites where it is deployed.

The module is composed of the following subparts:

- Fixed chassis or envelope attached to the rack (19" or ETSI),
- Swivelling chassis (left or right axis versions available) including a front patch panel with alphanumeric identifier for the adaptors,
- Pivoting support for the splice trays,
- Front output jumper management system,
- Device for lateral management of optical jumper harnesses.

The management of cables or protection tubes is done at the rear of the module whilst the management of the jumpers is performed at the front and on the rotation axis side.



STANDARDS

Aginode specification

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

COSH48 SC 2U Left axis version

Characteristics

结构特性

颜色	RAL 9002
柜式	19"/ETSI
材料	Steel painted

尺寸特性

深度	185 mm
高度	100 mm
接头数量	48
Cable Diameter	8.5 mm
高度单位	2 U
连接器数	48

使用特性

操作温度, 范围	-25...70 °C
最小弯曲半径 - 静态	30 mm
包装	箱