

# Outlets: @XS-Quad

## @XS-QUAD KIT - INDOOR CABLE 4FO (PULLING)

**Aginode Ref:** 10272959

- Up to **4 SC adapters**
- Wall mounted, on flush box or DIN rail
- No lid-opening to fix the outlet
- **Ready-to-fix** kit in option

Optical terminal outlets, installed in the subscriber's home, are the optical equipments materializing the demarcation between the FTTH operator network and the local subscriber's network.

Compact and ergonomic, its design has been studied in **partnership with SismoDesign agency** for a sober, discreet and elegant depiction, to fit at best at the inhabitant.

For security, adapters include an **automatic laser and dust protection**, called « internal shutter ».

The front side contains all the necessary indications (from top to bottom):

- Swiveling flap to protect and hide the identification label
- Area to stick Identification Label (under the flap)
- 4-colour identification code for the adapters
- Indication that polarizing slot is upwards
- Integrated laser symbol

The @XS-Quad outlets range comes in 2 families:

- The “equipped” outlet is provided with adapters and pigtails preinstalled. It must then be connected with the subscriber's cable.
- The “kit” outlet is provided pre-cabled, ready to be fastened without any outlet opening. Cable type and length are customizable.



## STANDARDS

Aginode specification  
Orange/France Telecom

# @XS-Quad Kit - Indoor cable 4FO (pulling)

## Characteristics

### 结构特性

颜色	白 RAL 9010
材料	Thermoplastic

### 尺寸特性

深度	25 mm
高度	80 mm
宽度	80 mm
直径范围	2...5 mm
接头数量	4
线缆长度	30 m
最大的适配器数	4

### 机械特性

IK Rating	5
-----------	---

### 使用特性

操作温度, 范围	-5...45 °C
适配器	SC/APC
耐火	UL 94 V0
最小弯曲半径 - 静态	15 mm
抗UV	是
包装	箱
防水	IP 50

## 文件

Installation @XS-Quad pdf — 2.69 MB [下载](#) ↓

ESERV\_PTOCablesStd\_EN\_1.xlsx xlsx — 10.27 KB [下载](#) ↓