

Outlets: @XS-Slim

@XS-SLIM KIT - OUTDOOR CABLE 1FO (DOUBLE SHEATH)

Aginode Ref: 10272963

- **1 SC adapters**
- Wall mounted, on flush box or DIN rail
- No lid-opening to fix the outlet
- **Ready-to-fix** kit in option
- **1 Keystone slot** for RJ45 or coaxial plug delivered within the Hybrid optional kit

Optical terminal outlets, installed in the subscriber's home, are the optical equipments materializing the demarcation between the FTTH operator network and the local subscriber's network.

Compact and ergonomic, its design has been studied in **partnership with SismoDesign agency** for a sober, discreet and elegant depiction, to fit at best at the inhabitant.

For security, adapters include an **automatic laser and dust protection**, called « internal shutter ».

The front side contains all the necessary indications (from top to bottom):

- Swiveling flap to protect and hide the identification label
- Area to stick Identification Label (under the flap)
- Indication that polarizing slot is upwards
- Integrated laser symbol

The @XS-Slim outlets range comes in 2 families:

- The “equipped” outlet is provided with adapter and pigtail preinstalled. It must then be connected with the subscriber's cable.
- The “kit” outlet is provided pre-cabled, ready to be fastened without any outlet opening. Cable type and length are customizable.



STANDARDS

Aginode specification
Orange/France Telecom

@XS-Slim Kit - Outdoor cable 1FO (double sheath)

Characteristics

结构特性

材料	Thermoplastic
颜色	白 RAL 9010

尺寸特性

宽度	80 mm
接头数量	2
最大的适配器数	1
深度	25 mm
直径范围	2...5 mm
线缆长度	50 m
高度	80 mm

机械特性

IK Rating	5
-----------	---

使用特性

包装	箱
抗UV	是
操作温度, 范围	-5...45 °C
最小弯曲半径 - 静态	11 mm
耐火	UL 94 V0
适配器	SC/APC
防水	IP 50

文件

Installation @XS-Hybrid/Slim pdf — 2.53 MB [下载](#) ↓

ESERV_PTOCablesStd_EN_1.xlsx xlsx — 10.27 KB [下载](#) ↓

@XS-FAST pdf — 981.89 KB [下载](#) ↓