LANmark-6A Cable

LANMARK-6A F1/UTP AWG23 CAT 6A LSZH CCA S1A D1 A1 ORANGE 1000M REEL

Aginode Ref: N100.622G-OC

- Ideal cable for 10GBase-T application
- Full compliance to latest standards for Category 6A and Class EA
- Guaranteed performance up to 500MHz
- Global screen offering Alien Crosstalk immunity
- Foil with aluminium side facing outwards providing easy bonding with connector
- Enhanced reaction-to-fire performance according to CPR classification Cca-s1a,d1,a1 (h/EN50575:2014+A1:2016)



STANDARDS

ANSI/TIA 568.2-D
EN 50173-1
IEC 61156-5
IEEE 802.3bt (PoE++)
ISO/IEC 11801
EN 50288

Application

LANmark-6A cables are the ideal solution for a 10G Ethernet network. The range has been designed specifically to support the higher frequencies required for 10 Gigabit Ethernet, while maintaining full backwards compatibility with today's needs. All LANmark-6A cables are shielded, in order to ensure immunity to Alien Crosstalk and other external interferences.

- 10Base-T Ethernet
- 100Base-TX Fast Ethernet
- 1000Base-TX Gigabit Ethernet
- 10GBase-T 10 Gigabit Ethernet IEEE 802.3
- 155 Mbit ATM
- 1.2 Gbit ATM
- future Cat 6A and Class EA applications
- PoE++ Type 4 (IEEE 802.3bt)

Performance

With guaranteed performance to 500MHz, Aginode LANmark-6A cables exceed the requirements of the International, European and American cable standards, including ISO/IEC 11801, IEC 61156-5, EN 50173, EN 50288 and TIA/EIA 568.2-D

When used in combination with Aginode LANmark-6A connectors and LANmark-6A Ultim patch cords, the system supports the 10GBase-T applications as defined in IEEE 802.3an and meets or exceeds the link and channel

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

requirements for Category 6A and Class EA as defined in TIA/EIA 568.2-D and ISO/IEC 11801.

Installation

To support the correct set-up of hand held analysers for installation testing, the actual cable NVP value is given in the cable's print legend.

Guarantees

Traceability codes on both cable and packaging ensure quality validation of the installed cable.

Installations with LANmark-6A cable and connectivity are qualified for a 25 year full system warranty, which includes Parts, Channel Performance, Application Support and Labour, as described in the Aginode Certified System Warranty.

Electrical Performance LANmark-6A F1/UTP Cable

Freq	Attn in dB		NEXT in dB		PSNEXT in dB		ACR-F in dB		PS ACR-F in dB		PS ANEXT in dB		PS AACR-F in dB		RL in dB	
in MHz	Max.	Typ.	Min.	Typ.	Min.	Typ.	Min.	Typ.	Min.	Typ.	Min.	Typ.	Min.	Typ.	Min.	Typ.
1	2,1	2,1	74,3	79,3	72,3	77,3	67,8	87,8	64,8	84,8	67,0	90,0	67,0	76,7	20,0	26,0
4	3,8	3,8	65,3	70,3	63,3	68,3	55,8	75,8	52,8	72,8	67,0	90,0	66,2	75,9	23,0	29,0
10	5,9	5,9	59,3	64,3	57,3	62,3	47,8	67,8	44,8	64,8	67,0	87,0	58,2	67,9	25,0	31,0
16	7,5	7,5	56,2	61,2	54,2	59,2	43,7	63,7	40,7	60,7	67,0	85,0	54,1	63,8	25,0	31,0
20	8,4	8,4	54,8	59,8	52,8	57,8	41,8	61,8	38,8	58,8	67,0	84,0	52,2	61,9	25,0	31,0
31,25	10,5	10,5	51,9	56,9	49,9	54,9	37,9	57,9	34,9	54,9	67,0	82,1	48,3	58,0	23,6	29,6
62,5	15,0	15,0	47,4	52,4	45,4	50,4	31,9	51,9	28,9	48,9	65,6	79,0	42,3	52,0	21,5	27,5
100	19,1	19,1	44,3	49,3	42,3	47,3	27,8	47,8	24,8	44,8	62,5	77,0	38,2	47,9	20,1	26,1
155	24,1	24,1	41,4	46,4	39,4	44,4	24,0	44,0	21,0	41,0	59,6	74,1	34,4	44,1	18,8	24,8
200	27,6	27,6	39,8	44,8	37,8	42,8	21,8	41,8	18,8	38,8	58,0	72,5	32,2	41,9	18,0	24,0
250	31,1	31,1	38,3	43,3	36,3	41,3	19,8	39,8	16,8	36,8	56,5	71,0	30,2	39,9	17,3	23,3
300	34,3	34,3	37,1	40,1	35,1	38,1	18,3	38,3	15,3	35,3	55,3	69,8	28,7	38,4	16,8	22,8
500	45,3	45,3	33,8	36,8	31,8	34,8	13,8	33,8	10,8	30,8	52,0	66,5	24,2	33,9	15,2	21,2

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

LANmark-6A F1/UTP AWG23 Cat 6A LSZH Cca s1a d1 a1 Orange 1000m reel

Characteristics

结构特性	
颜色	橙
外护套	低烟无卤
电缆类型	F/UTP
尺寸特性	
近似重量	52 kg/km
导体横截面尺寸（AWG）	23
绝缘外径	1.2 mm
标称外径	7.5 mm
电气特性	
特性阻抗	100 Ohm
20°C时导体的最大直流电阻	80 Ohm/km
最大转移阻抗在30MHz	120 Ohm/km
互电容	45 nF/km
机械特性	
最大操作抗拉强度	100 N
传输特性	
耦合衰减在30MHz	>70 dB
传播速度	68 %
传播延迟值，最大100MHz	536 ns/100m
时延值	45 ns/100m
使用特性	
环境安装温度，范围	-10...60 °C
类型	Cat. 6A
阻燃 - 火焰	IEC 60332-1
气体腐蚀性	IEC 60754-1; IEC 60754-2

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

长度	1000 m
最小弯曲半径 - 安装	60 mm
最小弯曲半径 - 工作	30 mm
操作温度，范围	-20...60 °C
包装	电缆盘
范围	LANmark-6A
烟密度	IEC 61034

文件

Freetable LM6A F1UTP V3_2.xls xls — 21 KB 下载

业绩声明

LANmark-6A F1/UTP AWG23 Cat 6A LSZH Cca s1a d1 a1 Orange 1000m reel pdf — 141.61 KB 下载

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.