

# LANmark-10G Cable

LANMARK-10G U/FTP AWG23 CAT 6A LSZH DCA S2 D2 A1 ORANGE 500M REEL

**Aginode Ref:** N10G.UF4-OD

- Ideal cable for 10GBase-T application
- Full compliance to latest standards for Category 6A and Class EA
- Guaranteed performance up to 500MHz
- Individual pair shielding offering Alien Crosstalk immunity

## Application

LANmark-10G cables are the ideal solution for a 10G Ethernet network. The range has been designed specifically to support the higher frequencies required for 10 Gigabit Ethernet, while maintaining full backwards compatibility with today's needs. LANmark-10G cables have individual pair shielding, in order to ensure immunity to Alien Crosstalk and other external interferences.

- 10Base-T Ethernet
- 100Base-TX Fast Ethernet
- 1000Base-TX Gigabit Ethernet
- 10GBase-T 10 Gigabit Ethernet
- 155 Mbit ATM
- 1.2 Gbit ATM
- future Cat 6A and Class EA applications

## Performance

With guaranteed performance to 500MHz, Aginode LANmark-10G cables meet the requirements of the International, European and American cable standards, including ISO/IEC 11801, IEC 61156-5, EN 50173, EN 50288 and TIA/EIA 568-C.2.

When used in combination with Aginode LANmark-10G connectors and LANmark-10G patch cords, the system supports the 10GBase-T applications as defined in IEEE 802.3an and meets the link and channel requirements for Category 6A and Class EA as defined in TIA/EIA 568-C.2 and ISO/IEC 11801.



## STANDARDS

ANSI/TIA-568-C.2  
EN 50173-1  
EN 50288-4-1  
IEC 61156-5  
ISO/IEC 11801

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

## Installation

The LANmark-10G cables have the advantage of offering equal dimensions and flexibility as the equivalent LANmark-6 screened cables with the same ease of installation and termination.

To support the correct set-up of hand held analysers for installation testing, the actual cable NVP value is given in the cable's print legend.

## Guarantees

Traceability codes on both cable and packaging ensure quality validation of the installed cable.

Installations with LANmark-10G cable and connectivity are qualified for a 25 year Aginode Link Warranty Certificate.

## Electrical Performance LANmark-10G Cable

Freq in MHz	Attn in dB Max.	NEXT in dB Min.	PSNEXT in dB Min.	ACR-F in dB Min.	PS ACR-F in dB Min.	PS ANEXT in dB Min.	PS AACR-F in dB Min.	RL in dB Min.
1	2,1	74,3	72,3	67,8	64,8	67,0	67,0	20,0
4	3,8	65,3	63,3	55,8	52,8	67,0	66,2	23,0
10	5,9	59,3	57,3	47,8	44,8	67,0	58,2	25,0
16	7,5	56,2	54,2	43,7	40,7	67,0	54,1	25,0
20	8,4	54,8	52,8	41,8	38,8	67,0	52,2	25,0
31,25	10,5	51,9	49,9	37,9	34,9	67,0	48,3	23,6
62,5	15,0	47,4	45,4	31,9	28,9	65,6	42,3	21,5
100	19,1	44,3	42,3	27,8	24,8	62,5	38,2	20,1
155	24,1	41,4	39,4	24,0	21,0	59,6	34,4	18,8
200	27,6	39,8	37,8	21,8	18,8	58,0	32,2	18,0
250	31,1	38,3	36,3	19,8	16,8	56,5	30,2	17,3
300	34,3	37,1	35,1	18,3	15,3	55,3	28,7	16,8
500	45,3	33,8	31,8	13,8	10,8	52,0	24,2	15,2

# LANmark-10G U/FTP AWG23 Cat 6A LSZH Dca s2 d2 a1

## Orange 500m reel

### Characteristics

#### 结构特性

颜色	橙
外护套	低烟无卤
电缆类型	U/FTP

#### 尺寸特性

近似重量	49 kg/km
导体横截面尺寸 (AWG)	23
绝缘外径	1.32 mm
标称外径	7.0 mm

#### 电气特性

特性阻抗	100 Ohm
20°C时导体的最大直流电阻	80 Ohm/km
最大转移阻抗在30MHz	120 Ohm/km
互电容	45 nF/km

#### 机械特性

最大操作抗拉强度	100 N
----------	-------

#### 传输特性

衰减串扰比, 250MHz	25 dB/100m
耦合衰减在30MHz	>70 dB
传播速度	82 %
传播延迟值, 最大100MHz	536 ns/100m
时延值	30 ns/100m

#### 使用特性

环境安装温度, 范围	0...50 °C
类型	Cat. 6A
阻燃 - 火焰	IEC 60332-1

气体腐蚀性	IEC 60754-1; IEC 60754-2
长度	500 m
最小弯曲半径 - 安装	56 mm
最小弯曲半径 - 工作	28 mm
操作温度, 范围	-20...60 °C
包装	电缆盘
范围	LANmark-10G
烟密度	IEC 61034

## 文件

Freetable LM6A UFTP V2.xls xls — 23.5 KB [下载](#) ↓

## 业绩声明

LANmark-10G U/FTP AWG23 Cat 6A LSZH Dca s2 d2 a1 Orange 500m reel pdf — 140.96 KB [下载](#) ↓