

LANmark-OF ENSPACE MPO-LC 模块

LANMARK-OF 超低损耗 ENSPACE MPO无导针-双工LC模块 交差线序 12芯 多模 OM5 柠檬绿 内嵌防尘门

Aginode Ref: NSPACE.MCLC12LS

- ENSPACE 模块前部有 12 个 LC 多模石灰绿适配器，后部有 1 个 MTP 适配器
- 模块内 MPO-12LC 光纤组件的超低损耗多模 OM5 性能
- 交叉布线
- 模块可轻松安装到安捷诺的 ENSPACE 配线架中
- 模块可从面板前后安装

ENSPACE MPO 3 LC MPO LC MPO LC
MPO MPO
LC LC LC
ENSPACE
12 ENSPACE MPO ENSPACE UHD 1U 12
1U 144 LC
8 ENSPACE MPO ENSPACE HD 1U 8
1U 96 LC
ENSPACE
TIA-568-C A B C
A A
B B
C C
ENSPACE MPO MPO
IEC 61300-3-45 IEC 61300-3-6

由于所有连接都已在工厂端接和测试，因此安装时间短，便于快速部署。



STANDARDS

ISO/IEC 11801

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.



LANmark-OF 超低损耗 ENSPACE MPO无导针-双工LC模块 交叉线序 12芯 多模 OM5 柠檬绿 内嵌防尘门

Characteristics

结构特性

颜色	柠檬绿
光纤类型	OM5 50/125
布线类型	交叉

传输特性

最大插入损耗, dB	0.35 dB
最小回波损耗, dB	20 dB
插入损耗, 典型值	0.2 dB

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

