SNAP-IN模块化配线架

LANMARK 24口倾斜式SNAP-IN配线架含电缆支架 - 黑色



Aginode Ref: N521.681BK

- 直面板带斜角式连接器固定架，可节省跳线导轨和机架空间
- 通用设计，支持非屏蔽和屏蔽卡入式连接器
- 坚固的钢结构
- 1 HU 上有 24 个端口
- 包括后部电缆支撑杆

LANmark面板角度连接器是一种屏蔽19"/1U配线架，带有一个固定托盘，最多可容纳24个普通RJ45/GG45卡入式连接器，这些连接器安装在面板内部的倾斜位置。

两侧各安装了 6 个双端口支架，这样就有 12 个连接器指向左侧，12 个连接器指向右侧。

由于双端口支架的角度设计，因此可以在 LANmark 面板上下没有任何电缆管理面板的情况下进行跳线。使用随配线架一起提供的蓝色 Keystone 夹可将卡入式连接器轻松安装到配线架上。 面板包装中不包含连接器，但包括 24 个用于SNAP-IN连接器的 Keystone 夹。

跳线板专为标准 19" 机柜设计，高 1U，支持以下常见功能：

- 正面颜色为黑色，与 RAL 9005 相似
- 专为屏蔽和非屏蔽卡入式连接器设计
- 兼容所有性能类别的连接器
- 提供 24 个端口；端口编号从左至右
- 坚固的钢结构
- UL94V-0

STANDARDS

Manufacturer specification

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

LANmark 24口倾斜式SNAP-IN配线架含电缆支架 - 黑色

Characteristics

结构特性	
颜色	黑
材料	钢
尺寸特性	
深度	75 mm
宽度	19 inches
高度单位	1 U
使用特性	
应用类型	固定安装
端口数	24
机械耐受度	良好的机械防护
包装	箱
抗振	高

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.