WALLDROP V2

WALLDROP V2 36OF





Aginode Ref: 10280445

WALLDROP 配备 3 个 12 OF 的接线盒

紧固套件：

- 配线电缆 10 至 12 毫米
- 5 至 7 毫米，用于跌落电缆

WALLDROP 光缆盒专为部署光缆而设计。其设计对视觉影响较小，最多可铺设 10 条辅助光缆或用户光缆。
其标准配置是一个可容纳 12 个接头的接头盒，可在现场扩展至 36 个接头，而不会中断连接（见扩展套件）。WALLDROP 接线盒可用于提取在线电缆上的微型模块，也可用作馈送垂降电缆的过渡点。可提供金属支架来固定电缆的强度件和/或芳纶，以用作接线盒。
下拉电缆入口处配有橡胶密封件和密封塞，孔径在 3 至 7 毫米之间（3-5 毫米和 5-7 毫米有两种密封类型）。用于直列电缆的横向分体式密封件可接受 6 至 12 毫米的电缆直径（3 种不同尺寸的密封件：6-8 毫米、8-10 毫米和 10-12 毫米）。
组织器托盘由不同的卷绕区组成，用于卷绕从主电缆和用户连接中提取的光纤或微型模块。主电缆固定在外壳外侧的电缆夹上。
接续盒有一个 1x4 裸光纤分路器插槽。
WALLDROP 盒可根据安装情况水平或垂直安装。也可以直接悬挂在电缆上安装。
产品随附安装所需的所有配件（梳子、盒、密封件、塑料扎带和墙壁安装套件）。
产品有浅灰色和黑色两种颜色可供选择。

STANDARDS

Aginode specification

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.

walldrop v2 36of

Characteristics

结构特性	
颜色	黑
材料	Thermoplastic
尺寸特性	
Diameter branch cable	5...7 mm
Diameter main cable	10...12 mm
高度	70 mm
长度	203 mm
Max. number of cables	10
最大安装卡座数量	3
接头数量	36
宽度	138 mm
机械特性	
IK Rating	8
使用特性	
安装类型	户外
最小弯曲半径 - 静态	15 mm
操作温度，范围	-40...65 °C
包装	箱
RoHS compliant	Yes
抗UV	是
防水	IP 55

文件

Instruction manual pdf — 5.25 MB 下载

Leaflet Facade Solution EN pdf — 5.07 MB 下载

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Aginode is indicative only and shall not be binding on Aginode or be treated as constituting a representation on the part of Aginode.